

بار قانون الماسح الضوئي PDF417 الروبوت 2D (نموذج: OCBS-2002)

المواصفات:

صورة الاستشعار	CMOS	
قرار	752 * 480	
مصدر ضوء	LED (نانومتر ± 10 نانومتر 630)	
شدة الضوء	300 LUX (130 مم)	
إضاءة	0 ~ 100000 LUX	
الرموز	2D	PDF417، مصفوفة البيانات، (نموذج 02/01)، رمز الاستجابة السريعة (ECC200، ECC000، 050، 080100140)، أزيك، Maxicode، LP، الخ، المدونة،
	1D	الصين وظيفة 25، CODE128، EAN-13، EAN-8، CODE39، UPC-A، UPC-E، Codabar، الخ، ISBN / ISSN، قانون 93، UCC / EAN-128، GS1 Databar، المعشق 2 من 5.
دقة	≥ 3MIL	
عمق الميدان المسح الضوئي	مم ~ 450 مم 5	
الطباعة على النقيض من الإشارة	≥ 25%	
لقة / الملعب / الإنحراف	360 ° / 60 ° / 55 °	
السطح البيني	بلوتوث / HID-POS / PS2-KBW / ميناء مضاهاة / RS232 / HID-KBW / UDP / USB COM	
استهلاك الطاقة	1.65 W	
الجهد الكهربى	DC 5 V	
تيار	ماكس	مللي أمبير 330
	العمل	مللي أمبير 290
	خامل	مللي أمبير 200
الوزن	غرام 250	
أبعاد	ملم 164 * 126 * 73	
العمل درجة الحرارة	C +45 ~ درجة C -5	
درجة حرارة التخزين	C +60 ~ درجة C -40	
رطوبة	(دون تكاثف) 5% - 95%	
البرمجة البرمجيات	لايت uTools، مجموعة السريع، دليل البرمجة	

تفاصيل المنتج:



ocom
All your side

**Handheld 2D
Barcode Scanner
OCBS-2002**



Product Picture





Features

Simple but not easy

Handheld barcode scanner
for 1D/2D



CMOS image technology base



High speed and precision decoding



RS232, KBW and USB interfaces supported



Ergonomics design, optional fixing stand, IP54 rating for a dust-proof & water-proof functionality



All-round show





Parameter

Image Sensor	CMOS	
Resolution	752 * 480	
Interface	RS232 / HID-KBW / UDP / USB COM Port Emulation / HID-POS	
Symbology	2D	PDF417, QR Code(Model 1/2), Data Matrix(ECC200, ECC000, 050, 080,100,140), Aztec, Maxicode, LP Code, etc.
	1D	Code128, EAN-13, EAN-8, Code39, UPC-A, UPC-E, Codabar, China post 25, Interleaved 2 of 5, ISBN/ISSN, Code 93, UCC/EAN-128, GS1 Databar,etc.
Precision	≥ 3mil	
Light Source	LED(630 nm ± 10 nm)	
Light Intensity	300 LUX (130 mm)	
Scanning Field	45 mm × 45 mm	

Depth of Scan Field		45 mm ~ 450 mm
Print Contrast Signal		≥ 25%
Roll		360°
Pitch		45°
Yaw		45°
Illumination		0 ~ 100,000 LUX
Power Consumption		1.65 W
Voltage		DC 5 V
Current	Max	330 mA
	Working	290 mA
	Idle	200 mA
Weight		250 g
Operate Temperature		-5°C - +45°C
Storage Temperature		-40°C - +60°C
Humidity		5% - 95%(non-condensing)
Programming Software		Quick Set, Programming Guide, uTools Lite
Certification		FCC Part15 Class B, CE EMC Class B

Shipping and payment

1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
2. EXPRESS: around 3-7 working days to arrive
3. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which destination port
4. By sea: depend on which destination port
5. T/T
6. Western Union
7. Escrow
8. L/C

Company Profile



OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.

We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: www.ocominc.com,
Together we quest for the best.



الوثائق ذات الصلة:

الوقود النووي؟ من فضلك انقر هنا [information](#) تريد أن تعرف المزيد من الوقود النووي المشع المنتج 

[مواصفة](#)