

سطح المكتب متعددة الاتجاهات قارئ الباركود  
(نموذج: OCBS-T005)

المواصفات:

المواصفات العامة	
نوع الترميز	650NM الترميز البصري (VLD)
نوع الترميز	0-200 مم (UPC / EAN 100 PCS = 90)
نوع الترميز	5 الترميز البصري
نوع الترميز	1400 الترميز البصري (الترميز البصري)
نوع الترميز	20
نوع الترميز	5mil @ PCS 90
نوع الترميز	30 @ UPC / EAN 100
نوع الترميز (LED)	نوع الترميز LED (الترميز البصري)
نوع الترميز	نوع الترميز البصري
نوع الترميز	نوع الترميز البصري RS-232C HID USB
الخصائص	
الارتفاع	139mmX 105mmX 200MM (الترميز)
الوزن	535g
نوع الترميز	2M
نوع الترميز	50 الترميز البصري
البيانات الكهربائية	
نوع الترميز	5VDC ± 10
نوع الترميز	1.35 W
نوع الترميز	270mA @ 5V (350 (الترميز)MA (الترميز)
البيانات البيئية	
نوع الترميز	0 degree C- 40degree C (F 32degree - 104 (الترميز) F)
نوع الترميز	-20degree C - 60degree C (-4 (الترميز) C - 140 (الترميز) F)
نوع الترميز	5 ~ 90 RH (الترميز) (الترميز)
نوع الترميز	(الترميز) (الترميز) 4000 (الترميز) (الترميز)
نوع الترميز	1.0 (الترميز) (الترميز) (الترميز)M (الترميز) (الترميز)
البيانات الامتثال	
نوع الترميز	CDRH (الترميز) (الترميز) IEC 60825-1: (الترميز) (الترميز)
EMC	CE EN55022 B (الترميز) (الترميز) 15 (الترميز) (الترميز) (الترميز) (الترميز) VCCI BSMI

تفاصيل المنتج:



*Omni-Directional  
Barcode Scanner*

**OCBS-T005**



Product Picture





## Features

### *Simple but not easy*

High performance 32 bit hardware decoding ;



NICAM power design, suitable for



noisy environments;

Multiple/Single line scanning capability,  
meet different requirement;



Multiple interfaces: PS/2,  
RS232 or USB



## ||| All-round show



## Parameter

<b>Operational</b>	
Light Source	650nm visible laser diodes (VLD)
Depth of Scan Field	0 - 200 mm (UPC/EAN 100%, PCS=90%)
Scan Pattern	5 directions of scan field
Scan Rate	1400 scans per second (omni-directional)
Number of Scan Lines	20
Minimum Barcode Width	5mil @ PCS 90%
Print Contrast	30% @ UPC/EAN 100%
Indicators (LED)	Two-color LED (blue & red)
Beeper Operation	Programmable tone and volume
System Interfaces	Keyboard wedge, RS-232C, HID USB
<b>Physical</b>	
Dimension	139mmX 105mmX 200mm (LxWxH)
Weight	535g
Cable Lenth	2M
Tilt	50° forward
<b>Power</b>	
Input Voltage	5VDC ± 10%
Power	1.35 W
Operating Current	270mA @ 5V (Normal); 350mA (Max)
<b>Environmental</b>	

Operating Temperature	0°C - 40°C (32°F - 104°F)
Storage Temperature	-20°C - 60°C (-4°C - 140°F)
Humidity	5% ~ 90% RH, non-condensing
Light Levels	Up to 4000 Lux (fluorescence)
Drop Durability	Designed to withstand 1.0M drops to concrete surface
<b>Regulatory</b>	
Laser Class	CDRH Class IIa; IEC 60825-1: Class I
EMC	CE EN55022 B FCC Part 15 Class B VCCI, BSMI

## Shipping and payment

1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
2. EXPRESS: around 3-7 working days to arrive
3. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which destination port
4. By sea: depend on which destination port
5. T/T
6. Western Union
7. Escrow
8. L/C

## Company Profile



OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.





We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: [www.ocominc.com](http://www.ocominc.com), Together we quest for the best.



## الوثائق ذات الصلة:

الوقود النووي؟ من فضلك انقر هنا information تريد أن تعرف المزيد من الوقود النووي المشع المنتج

[مواصفة](#)