

□□□□□□ □□□□		33.2 □□□□ □°44 □□□□°
□□□ □□□□□□□□	EAN-13	0CM-20CM(13mil)
	PDF 417	0CM-7CM(6.67mil)
	39 □□□□□	0CM-12CM(5mil)(1 □□□)
	□□□□□□□ □□□□□□□	0CM-4CM(10mil)
	□□□ □□□□□□□□ □ □□□□□□□	0CM-10CM(15mil)
□□□□□□□(L * W * H)		89 * 108 * 143mm(2 □□□□□)
□□□		245G(□□□ □□□□ □□□)
□□□□□□□ □□□□□ □□□□		20°C ~ + 50°C (-4°F ~ 122°F)
□□□□□ □□□□ □□□□□□□		-40°C ~ + 80°C (-40°F ~ 176°F)
□□□□□		5□ ~ 95□(□□□□□ □□□)
ESD		±14 □□□□□□□□□□ □□□□ □□□□ 8± □(□□□□□□ □□□□□□)□□□□ □□□□ □□□□□□□□
□□□□		1.2 □□□ □□□□□ □□□□ □ □□□□□ □□□□□) □□□□□□□□□ □□□□□ □ □□□□□
□□□		IP 52



OCBS-T203



www.ocominc.com

