

- \* 11 EPSON
- \* 5 V 24
- \* 20-x 2
- \* POS.
- \* O POS / J POS

Technical Specifications

Resolution	Resolution	Resolution (dots/mm)
Resolution	Resolution	40 (20 ×)
Resolution	Resolution	500 ~ 1000 cd / m <sup>2</sup>
Resolution	Resolution	5 × 7
Resolution	Resolution	95 Alphanumeric 32 International Characters
Resolution	Resolution	5.25 (x) x 9.02 (H) (mm)
Resolution (X x Y)	Resolution	0.86 × 1.05 (mm)
Resolution	Resolution	9
Resolution	Resolution	220 (mm) (mm) 125 × (mm) 45 × (mm)
Resolution	Resolution	140 (mm) (L) × 34.5 (mm)
Resolution	Resolution	205 (mm) (mm) 33 × (mm) 106 × (mm)
Resolution	Resolution	90 °
Resolution	Resolution	355 °
Resolution	Resolution	980
Resolution	Resolution	LD220 EPSON POS D101 AEDEX UTC / S UTC / P ADM788 DSP800 CD5220 EMAX LOGIC CONTROL
Resolution	Resolution	DENMARKI, DENMARKII
Resolution	Resolution	RS-232 / USB
Resolution	Resolution	19 200 9600
Resolution	Resolution	MTBF 30000
Resolution	Resolution	5 ~ 24 VDC
Resolution	Resolution	EMC FCC CE

