

15 .6 POS

(M/N:POS -L 15 6)

OCOM POS-L156 pos O

- l. I3 I5
- m. Msata SSD 64 GB SSD 128GB 256 GB
- n. 58mm 80mm
- o.
- p. MSR VFD220
- q.

	POS-L 156
	15.6 POS
	15.6
	1366*768
	25 0cd/m ²
	1 60 1 50
	G+G
	15.6 / 1366*768
	2*20 VFD
	Intel Celeron Bay Trail J1900 2.0GHz Intel Celeron J4125 Intel Core I3 / I 5 CPU
	1*SO-DIMM DDR3L 4GB DDR3L/ 1333 MHZ 8GB
	Msata SSD 64GB 256GB
	Real Tek ALC662
	10/100Mbs Realtek RTL8111F
	Mini PCI-E WIFI
	Windows 7/8/10 WEPOS Linux
	*1
	12V DC *1
	LAN RJ-45*1 RJ11
	USB*6
	15PIN D-sub VGA *1
	RS 232*1
	*1 *1
80mm	
	1 5 0mm/s
	79.5-/+ 0.5mm 72mm
	50km
58mm	
	85mm/s
	57.5-/+ 0.5mm 48mm
	50km
MSR	MSR
	4ohm/5w
	6.5 8.0 15.6
	490 * 31 0 * 48 5
	110-240V /50-60HZ DC12/5A W/o W/ 58mm DC12V/7A W/ 80mm

Dual Screen POS Machine

Model: POS-L156



WINDOWS



LINUX



J1900, J4125 or
i3 / i5 for option



Memory
4G or 8G



Msata SSD
64GB or higer



Built in 58mm
or 80mm printer



Built in 1D&2D
barcode scanner



15.6 inch touch
screen monitor



HD Capacitive Screen

15.6-inch multi-point projected capacitive touch panel with 1366*768 resolution

Water proof

Oilproof

Dustproof Front Screen



Built-in Thermal Printer

Built-in 80mm thermal printer with auto-cutter or 58mm thermal printer without auto-cutter for optional



Application



Bar



Restaurant



Coffee Store



Mile Tea Store



Bakery



Convenience Store



Library



Supermarket

FACTORY STRENGTH



