

300DPI

m / n OCBP-012a / b

200 MHz 32 RISC

8 MB SDRAM + 8 MB

127 5

300 984'

203 DPI 300dpi

Bartender Label Edition

	OCBP -012A	OCBP -012B.
	8 / mm 203 dpi	12 / mm 300 dpi
	127 mm 5 / s	101.6 mm 4 / s
	108 mm 4.25"	104 mm 4.09"
	1178mm 70	889 35"
	20-112mm 0.78"-4.4"	
	0.06 0.254 mm 2.36 10	
	10 1178 mm 0.39" 70"	10 889 mm 0.39" 35"
	127 mm 5" OD	
	300 OD 67 mm 1" 40 mm 110 mm 1.6" 4.3"	
	299 mm d x 235 mm w x 198.3 mm h	
	2.55kg.	
	32 RISC CPU	
	8MB 8MB SDRAM. SD 4 GB	
	<ul style="list-style-type: none"> •USB2.0 •RS-232 • 10/100 Mbps • 802.11 B / G / N 	
	AC 100-240V 1A 50-60Hz DC 24V 2.5A 60W	
	LED 1 1 LED 3	
	8	
	TTF	

□□	1D□□□□□□39□□□□93□□□□128UCC□□□□128□□A□B□C□Codabar□□□□2□ean-8□EAN-13□EAN-128□UPC-A□UPC-E□EAN□UPC 2□5□□□□□□□MS□Plessey□POS TNET□□□□POST 2D□□□□PDF-417□Maxicode□DataMatrix□QR□
□□	Bimap□BMP□PCX□□□□256□□□□
□□□□□□□□	0°□90°□180°□270°
□□□□□□	TSPL.
□□	□□□□5□40°C□25□85□□□□ □□□□-40□60°C□10□90□□□□
□□	①Windows□□□□CD□;②□□□□;③USB□;④□□□□;⑤□□□□□□□□;⑥□□□□□□□□x 2□1.5"□□□□□x 2;⑦□□□□;⑧media
□□□□□□	□□□□□□□□□□□□□□□□□□□□□□0.06□0.19mm□500000□□; 0.20□0.25mm□200000□□□□
□□□□	□□□□□□□□□□OD□ 214□□□□8.4"□□25.4□□□1"□□□□□□□□□□□□□□□□□□□□□□802.11 B / G / N□□□□□□□□□□RFIDModule□





OCBP-012





OCBP-012





OCBP-012





OCBP-012

