

□□	- T2
□□	5.5□□ □□□□□□□□ □□□□□□
□□	3.8 □ / 64 00□□□□
□□□□□	□□□100-240V , 50/60□□ ,1.5A □□□ 5 V □□ /2 A
□□□□□	USB C □
□	
□□□	5.5□□□□□□□□ □□
□□	720*1280 IpS
□□	
□□□□□	□□MT6797 Tri-Cluste-A72*2A53*8 2.3GHz□□□□
□□	3 □□
□□	16GB□□
□□	2G/3G/ 4G
□□□□	□□ 8.0
□□	□□□□□□□□□□ ,□□□□□
□□	□□4.0
□□□□	WIFI 802.11 bgnac
□□□□	58mm □□□□ □□□□ □□□□
□□	□□□58mm□□□□□≤40mm
□□□□	5□□□ □□□□□ , 2D □□□□□□□□
□□□□	□□ISO/IEC 14443A&B□Mifare□felica□
SIM□□	Sim*2□□□□□□□□Sim*1Sam*1□□□□□
□□□□	□□□□□□□□□□
□□ p □□	□□□□□□/STQC □□ p □□ □□□□□□
GPS □ AGPS	□□GPSAGPS
□□□□□	□□
□□□□□	
□□	USB C □*1
	□□ □□□*1
	□□□□*1
□□	
□□□□	0 □ 40 □□□□
□□□□	- 10 □ 60 □□□□
□□□□	10%~80%
□□□□	10%~90%

POS Terminal with Thermal Label and Receipt Printer

Model: POS-T2



»» Features:

- 5.5-inch Handheld Android POS Terminal
- Deca-core MT6797 Tri-Cluste-A72*2+A53*8 2.3GHz processor
- Built-in high speed 58mm thermal receipt and label printer
- Standard 3GB RAM+16G ROM
- Built-in large volume speaker
- Built-in NFC Module
- 2*SIM card slot
- Support USB type-C fast charging
- Removable 6400mAh large capacity battery
- 1D&2D Bar code reader and fingerprint for option

»» Productl Details:



»» Productl Specification:

General	
Model	POS-T2
Name	5.5 inch capacitive touch screen, support the electronic signature
Battery	3.8 V/6400mAh
Power adapter	Input: 100-240V, 50/60Hz, 1.5A Output: 5V DC /2A
Charger interface	USB type C
Display	
Main screen	5.5 inch HD touch screen dispaly
Resolution	720*1280 IPS
Performance	
CPU	Deca-core MT6797 Tri-Cluste-A72*2+A53*8 2.3GHz processor
RAM	3GB
Flash	16GB Flash
Communication	2G/3G/4G
Operating system	Android 8.0
Button	Power button, Scan Button, Volume button
Bluetooth	Bluetooth 4.0
WIFI	WIFI 802.11 b.g.n.ac
Printer	58mm Thermal Receipt and label Printer
Paper roll	Width: 58mm; Diameter: ≤40mm
Scanner	5 Mega-pixel Camera decoding, 2D Scanner (optional)
NFC	Support ISO/IEC 14443A&B, Mifare, felica card
SIM slot	Sim*2 (default) or Sim*1+Sam*1 for option
Speaker	Digital Audio speaker
Fingerprint	FBI/STQC Fingerprint (optional)
GPS or AGPS	Support GPS+AGPS
MDM	Support
Peripheral accessories	
Accessories	USB type C*1 Charging adapter*1 User manual*1
Environment	
Operating temperature	0 to 40 degrees centigrade
Storage temperature	-10 to 60 degrees centigrade
Working humidity	10%~80%
Storage humidity	10%~90%