

58 80mm 80mm

OCPP- M06)

OCPP-M06 Android IOS Android Window Linux JAVA 58 80mm
pos USB RS232 80mm 80mm
80mm CE FCC

OCPP



OCPP-M06

Windows Java Linux Android Android IOS

USB RS232

Android

8 7 visa

1500mm), 4~5mm

OCPP-M06

90mm/sec

50KM

OCPP

ESC/POS

□□□□

□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□ Mini□□□□□□□□□□TAXI□□□□□□□□
□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□ Mini□□□□□□□□□□□□□□□□

□□□

□□	
□□	OCP-06
□□	58mm □□□□□□□□□□
□□	□□□
□□	USB□RS-232□□□□□□□□
□□	7.4V DC/ 1500mAh□□□□□□□□
□□□□□	□□ 9v/1.5-2A
□□□□	□□□□4-5□
□□	□□□□□□□□20K□□□□256K
□□□□	□□□□□□□□□□□□□□&□□□□□□
□□□□	□□□
TPH □□	50KM
□□	□□□□□□“1234”□□□□□□□□□□□□□□6□
□□	□□□□□□□□□□□□□□□□□□□□
□□□□□□	3.5*1.1mm
□□□□□□	Windows & Android & IOS □□
□□□□	CE□FCC□Rohs□
□□□□	
□□□□	□□□
□□□	203DPI□8 □/□□□
□□□□	70 □□/□□□□ 90 □□/□□
□□□□	48mm
□□□□	120 □□□□□□□□□□
□□□□	□□A□32□□/□ □□□□□□16□/□
□□□□	□□□□/POS

□□□□□□	
□□□□	FontA: 12*24dots, 1.5(W)*3.0(H) □□/□□□24*24□□3.0(W)*3.0(H)mm
□□□	□□□□/□□
□□	
□□□□	□□□□
□□□□	57.5±0.5mm
□□□□	□□□□
□□□□	□□ 40 □□
□□□□	0.06-0.08mm
□□	
□□	105*75*45mm
□□	□□□360g □□□440g
□□□	190*120*70 □□
40□□□□	380*475*340mm/18.36kg
□□	
□□□□□	0□45□□□□10%~80% □□□
□□□□□	-20 □ 60 □□□□10%~90% □□□

58mm Portable Thermal Printer

Elegant and fashion design
Portable and small, easy to carry anywhere



Multiple connection methods compatible with multiple systems

Supports three different connection methods of Bluetooth, RS232 and USB, compatible with multiple System, multiple ways to print beyond your imagination.



High speed printing Clear and stable

90mm/s high speed printing, low noise, clear and stable printing, long time standby , instantly improve printing efficiency.



90mm/s

Max Print Speed



Large-capacity lithium battery long-term standby

Built-in 1500mAh large capacity removable lithium battery,
continuous long time Print, and longer standby time.



5 Hours

Continuous printing time



200 m

Full power printing

1500
mAh



MINI Thermal Printer
Model:OCPP-58
Paper Width:58mm
Power Supply:5V/1.5A
S/N:OCPP-58-1
CE FC China

Li-ion Battery

Vol:7.4V/1500mAh/11.1Wh
Charge up Voltage: 8.4V
Standard:GB/T 18287-2000
One year warranty
Model:58LYDD-ZJ
Charge temperature:0°C to+45°C
Working temperature:-10°C to+60°C
Storage temperature:0°C to+35°C



S/N:JH202204251058DY0021
SHENZHEN XINXIONGLI ELECTRICAL Co.,LTD

Easy Paper Loading

No Ink No Ribbon

Thermal printing, cost saving, easier to change paper, sustainable high-efficiency printing

58mm

Maximum
paper width

40mm

Maximum
paper diameter



Support Three Charging Modes

Efficient and intimate

Three charging methods can be selected:
rechargeable battery, power adapter, or car charger.

Fast charging for outdoor use, more intimate.



**Power
Adapter**

**Rechargeable
Battery**

**Car
Charger**

Dimensions

Wireless Barcode Scanner



Packaging accessories

SMART-PRINTING



Beautiful packaging, original accessories



01 Machine 02 User Manual 03 Roller Paper

04 USB Cable 05 Charging Adaptor



□□□□

*□□

*□□□

*□□□□

*□□□ Windows □□□□

*Linux □□□□

*□□□□□□□□

*USB Printdemo(□□□□□□)

*Bluetooth Printdemo(□□□□□□)

* SDK □□□□

*□□□□