

OCBS -LA09

OCBS -LA09

OCBS

| | |
|------|--|
| OCBS | 650nm |
| OCBS | 200 |
| OCBS | 32 |
| OCBS | 2.5~600mm 100 UPC / EAN |
| OCBS | 50mm @ 60mm 220mm @ 200mm |
| OCBS | |
| OCBS | |
| OCBS | 3mil / 5mil |
| OCBS | 30 |
| OCBS | UPC / EAN UPC / EAN UCC / EAN 128 Code 39 Code 39 ASCII Trioptic Code 39 Code 128 Code 128 Full ASCII Codabar Interleaved 2 of 5 Discrete 2 of 5 Code 93 MSI Code 11 RSS 2 of 5 MSI / Plessey UK / Plessey UCC / EAN 128 GS1 DataBar RSS |
| OCBS | ±65°; ±60°; ±42° |
| OCBS | |
| OCBS | PS2 RS232 USB |
| OCBS | 5V DC±5 |
| OCBS | 85 mA; 100 |
| OCBS | LED |
| OCBS | ABS + PC |
| OCBS | |
| OCBS | 156 * 68 * 83 mm * * * |
| OCBS | 235 |
| OCBS | |
| OCBS | |
| OCBS | 0°C 45°C |
| OCBS | -40°C 60°C |
| OCBS | 5-90 |
| OCBS | +/- 15KV +/- 8KV |
| OCBS | 0~100,000 LUX |
| OCBS | 1.5 |
| OCBS | EN60825-1 Class 1 |

OCBS



ocom
All your side

*Handheld Laser
Barcode Scanner*

OCPP-LA09



Product Picture





Features

Simple but not easy

200scan/sec high scan rate and long reading distance;





Excellent decode capability;



KBW, RS232 and USB supported;



Durable construction combined with future-proofing





Competitive price for 32bit model



|| All-round show





Parameter

| Performance Characteristics | |
|-----------------------------|---|
| Light Source: | 650nm visible |
| Scan Rate: | 200 scans per second |
| CPU | 32 bit |
| Reading Distance | 2.5 ~600mm (100% UPC/EAN) |
| Width of Scan | 50mm@60mm, 220mm@200mm |
| Scanner Type: | Bi-directional |
| Operation mode | Auto Sense |
| Resolution: | 3mil high resolution series / 5mil long depth field series |
| Print Contrast Minimum: | 30%, minimum reflective difference |
| Decode Capability: | UPC/EAN, UPC/EAN with Supplementals, UCC/EAN 128, Code 39, Code 39 Full ASCII, Trioptic Code 39, Code 128, Code 128 Full ASCII, Codabar |

| | |
|---------------------------------|---|
| | Interleaved 2 of 5, Discrete 2 of 5, Code 93, MSI, Code 11, RSS variants, Chinese 2 of 5, MSI/Plessey, UK/Plessey, UCC/EAN 128, chinese code , GS1 DataBar (RSS) series |
| Scanning Angle | ±65°(tilt); ±60°(pitch); ±42°(yaw) |
| Physical Characteristics | |
| Interfaces Supported: | PS2, RS232, USB |
| Voltage: | 5V DC±5% |
| Current: | 85 mA (Operating); 100 (Max) |
| Indicator | Beeper, LED |
| Material | ABS+PC |
| Stand | Optional |
| Dimensions: | 156*68*83 mm (L*W*H) |
| Weight: | 235g |
| Color: | Grey and black |
| User Environment | |
| Operating Temperature: | 0°C~45°C |
| Storage Temperature: | -40°C~60°C |
| Humidity: | 5%-90% (non-condensing) |
| Electrostatic Discharge: | Conforms to +/-15KV air discharge and +/-8KV of contact discharge |
| Ambient Illumination | 0 ~ 100,000 LUX |
| Drop Specifications: | Withstands multiple 1.5m drops to concrete surface |
| Laser classification | EN60825-1, class 1 |

Shipping and payment

1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
2. EXPRESS: around 3-7 working days to arrive
3. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which

3. INTERNATIONAL AIR MAIL, usually around 2-4 days to arrive, will also depend on which destination port
4. By sea: depend on which destination port
5. T/T
6. Western Union
7. Escrow
8. L/C

Company Profile



OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.

We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: www.ocominc.com,
Together we quest for the best.

