

OCBS-LA12



OCBS-LA12

1. 1 x OCBS-LA12 Handheld Barcode Scanner

2. 200 x 200mm / 8" x 8" Base

3. 1 x 1.5m Cable

4. KBW, RS232, USB

5. 1 x 1.5m Cable

6. 1 x 1.5m Cable

OCBS-LA12

OCBS-LA12	
Wavelength	650-670nm
Resolution	200 dpi
Dimensions	2.5 x 600mm x 100mm UPC / EAN
Weight	300g
Scanning Speed	PCS 0.9 x 0.10mm x 400
Laser Power	30mW @ 650nm
Resolution	1/3000000
Barcode Types	UPC / EAN, 128, 39, 39 ASCII, 128, 128 ASCII, 2 of 5, 2 of 5 MSI, 11, ATA, RSS, 5 of 2
OCBS-LA12	
Connectivity	PS2, RS232, USB

電圧	5V +/- 5%
電流	100mA
消費電流	<40 mA
通信規格	RS232C
傾斜角	45°/60°
外形寸法	165mm X 63mm X 87mm
重量	129g
材質	樹脂
色	黒色
付属品	
電圧範囲	0~40V
電流範囲	-40~60mA
電圧精度	5% (95%)
電圧変動	+/- 15KV (電圧) +/- 8KV (電流)
電圧変動	1.5mV (電圧)
電圧	
EMI / RFI	FCC A CE
電圧	CDRH 2



OCBS-LA12





OCBS-LA12





OCBS-LA12





OCBS-LA12





OCBS-LA12



OCBS-LA12

OCOM 1D POS 500 1

OCOM DOT POS POS ISO CE FCC BIS

2007 6 OCOM ISO9001 2008 159 / 2300 50 O2 Equicom ...

OCOM " " ...

□OEM / ODM□

□□□□□□□□

▶ Company



▶ Certificates



▶ Payment



□□□□□□□□

· POS □□□□□□□□□□□□□□□□□□

· □□□□□□500□□□□□□□□

· 1□□□□□□□□□□□□□□02□Star ...

· □□163□□□□/□□□2600□□□□□□

· □□□□□□□□□□□□24□□□□□□□□

· □□12□OEM / ODM□□□□□□□□□□

· □□□□□□□□□□□□□□□□

· □□ISO 9001□FCC□CE□Rohs□Soncap□SASO□POA□BIS□□□□□□□□□□

· □□□□□□□□□□□□□□□□□□□□□□

· □□□□□□□□12 + 1□□□□□□□□□□□□□□

· □□“□□□□□□”

· □□□“□□□□□□□□□□□□□□□□□□□□□□”□□□□□□□□



