

4

M / N OCBP -004A / B

8 MB SDRAM 200 Mhz 32 RISC 4 MB

127 5

300 984' 25.4 1

Kiosk

TSPL-EZ™ TPLE TPLZ

|     | OCBP -004A   | OCBP -004B        |
|-----|--|-------------------|
|     | 8 / mm 203 DPI   | 12 / mm 300 DPI   |
|     |  |                   |
|     | 127 5 /  | 101.6 4 /         |
|     | 104 4.25   | 104 4.09          |
|     | 2794 110   | 1016 40           |
|     |  |                   |
|     | 20-112mm 0.78"-4.4"  |                   |
|     | 0.06~0.254 mm 2.36~10 mil  |                   |
|     | 10~2,794 0.39"~110"  | 10~1016 0.39"~40" |
|     | 127 5  |                   |
|     | 300 67 mm 1" 40 mm~110 mm 1.6"~4.3"  |                   |
|     |  |                   |
|     | 234 x 194.8 x 302.5  |                   |
|     | 3.1 6.83   |                   |
|     | 32 RISC CPU  |                   |
|     | 4MB Flash Memory   |                   |
|     | 8MB SDRAM  |                   |
|     | SD 4 GB  |                   |
|     | <ul style="list-style-type: none"> <li>•USB2.0</li> <li>•RS-232</li> <li>•Centronics</li> <li>•10/100 Mbps</li> <li>•802.11 b / g / n</li> </ul> |                   |
|     |  |                   |
|     | AC 100-240V 1A 50-60Hz   |                   |
|     | DC 24V 2.5A 60W  |                   |
| LED | 1 1 1 LED 3  |                   |

|          |   |
|----------|---|
| □□□      | □□□□□□□□ position□□□  |
|          | □□□□□□□   |
|          | □□□□□□□   |
|          | □□□□□□□   |
| □□□□     | □□  |
| □□□□     | 8□□□□□□□□□□<br>□□TTF□□□□  |
| □□       | 1D□□□Code 39□Code 93□Code 128UCC□Code 128□A□B□C□Codabar□Interleaved<br>2 of 5□EAN-8□EAN-13□<br>EAN-128□UPC-A□UPC-E□EAN□UPC 2□5□□□□□□MSI□PLESSEY□POS TNET□□□POS T<br>□□□□□PDF-417□Maxicode□DataMatrix□□□□□ |
| □□       | BIMAP□BMP□PCX□□□256□□   |
| □□□□□□□□ | 0°□90°□180°□270°  |
| □□□□□□   | TSPL□EPL□ZPL□DPL□   |
| □□□□     | □□□5~40°C□25~85□□□□□<br>□□□-40~60°C□10~90□□□□□  |
| □□□□     | FCC□CE□CCC□CB   |
| □□□□     | □□RoHS  |
| □□       | ①Windows□□□□CD□;②□□□□□□;③USB□□;④□□□□;<br>⑤□□□□□□□□□;⑥□□□□□□□□x 2,1.5"□□□□x 2;<br>⑦Ribbon□□x 2;⑧Ribbon□□;⑨□□   |
| □□□□     | □□□□□□10/100 Mbps□RS-232□Centronics□□□□□  |
| □□□□□□   | □□□□□□□□□□□□□□□□□□□□□□0.06~0.19mm□<br>□□500000; 0.20~0.25mm□□□20□   |
| □□□□     | □□□□□□□□□OD□ 214□□□8.4□□□□25.4□□□1□□□□□□□□□□□□<br>□□□□□□□□□□802.11 b / g / n□□□□□□□□□□□□RFID□□□□  |

**Product show:**



□□□□□

[OCOM.com](http://OCOM.com)