

1D / 2D

OCBS -F2200

□□

- ñ □□□□□□□□
- ñ □□□□□□□□□□
- ñ □□□□□□1D□2D□□□□□□□□
- ñ □□□□□□□□□□□□□□□□□□
- ñ 4mil□□□□□□□□;
- ñ □□□□□□□□

□□

□□□□

□□□□		
□□□	CMOS	
□□□	640 * 480,256□□	
□□□□□□	1300□UPC 40□□/□	
□□□□	□□50□□□20□	
□□	≥400□	
□□□□	□□	UPC-A□UPC-E□UPC-E1□EAN-13□EAN-8□ISBN□Bookland EAN□□ISSN□ Code 39□Code 39□ASCII□Code 32□Trioptic Code 39□□□2□5□□□2 5□□5 □2□□5□□□2□Codabar□NW7□□Code 128□UCC / EAN 128 □GS1-128□□ISBT 128□Code93□Code 11□USD-8□□MSI / Plessey
	2D	PDF417□MicroPDF417□QR□□DataMatrix□Han Xin□□Aztec□□GS1 Com pos ite
□□	□□39□500□□□50□□□120□□ □□39□1000□□□25□□□250□□ UPC / EAN□1300□□□20□□□320□□ □□□□750□□□63□□□150□□ PDF417□660□□□62□□□145□□	
□□□	□□±45°@ 0°□□□0°□□ □□±30°@ 0°□□□0°□□ □□±45°@ 0°□□□0°□□	
□□		
□□	USB□RS232	
□□□□	3.3v□5v□□	
□□□□	2.0w□400mA□	
□□□□	2.5w□450mA□	
□□□□□	□□5.5V 1A	
LED □	I□	
EMC □□	FCC part15□IEC60825-1□EN55022 B□	
□□□□		
□□□□	-20□□□□+60□□□□-4□□144□□	
□□□□	-30°C□+70°C□-22°F□158°F□	
□□	5□-95□□□□□□□□	
□□□□	1.5m□5.0ft□□□□□□□□	
□□□	□□□□□□□□□□□□	



F2200



www.ocominc.com

