

OCBS-F2200

OCBS

- ñ 1D/2D;
- ñ 4mil;
- ñ 1D/2D;
- ñ 4mil;
- ñ 1D/2D;
- ñ 4mil;

OCBS

OCBS

OCBS	CMOS
OCBS	640 * 480,256
OCBS	13mil UPC 40cm / s
OCBS	50; 20
OCBS	4mil
OCBS	UPC-A, UPC-E, UPC-E1, EAN-13, EAN-8, ISBN, Bookland EAN, ISSN, Code 39, Code 39 full ASCII, Code 32, Trioptic Code 39, Interleaved 2 of 5, 2/5, Codabar, NW7, Code 128, UCC / EAN 128, GS1-128, ISBT 128, Code 93, Code 11, USD-8, MSI / Plessey
OCBS	1D
OCBS	2D
OCBS	PDF417, MicroPDF417, QR Code, DataMatrix, Aztec Code, GS1 Composite
OCBS	Code 39, 5mil, 50, 120
OCBS	Code 39, 10mil, 25, 250
OCBS	UPC / EAN, 13mil, 20, 320
OCBS	7.5mil, 63, 150
OCBS	PDF417, 6.6mil, 62, 145
OCBS	±45° @ 0°, 0°
OCBS	±30° @ 0°, 0°
OCBS	±45° @ 0°, 0°

OCBS	USB, RS232
OCBS	3.3v, 5v DC
OCBS	2.0w, 400mA
OCBS	2.5w, 450mA
OCBS	DC, 5.5V 1A
OCBS	LED
OCBS	EMC, FCC, IEC60825-1, EN55022 B

OCBS	-20, +60, -4, 144
OCBS	-30°C, +70°C, -22°C, F, 158
OCBS	5 - 95
OCBS	1.5, 5.0
OCBS	



# F2200



[www.ocominc.com](http://www.ocominc.com)

