

CCD  
OCBS -C006

Product Description

2500 CCD  
280  
3  
/ /  
3  
3

		32 ARM
		2500 CCD
		LED 660nm±10nm
		280
		55° ±25° ±75°
		60 25mil 40cm 15mil 32cm 10mil 22cm 5mil 11cm 3mil 3cm
		≤110mm
		≥0.1 4
		15
		Code 39 Full ASCII Code 39 Code 32 Code 128 Code 93 Code 11 Codabar / NW7
		UPC / EAN / JAN EAN-13 EAN-8 UPC-A UPC-E EAN-128 Interleave 2 of 5 STD 2 of 5 Industrial 2 of 5, WPC
	2 of 5 Pos tage Code IATA MSI / PLESSY Industrial 2 of 5 BC-412 UPC-A UPC-E Code 128 Code 93 Coda bar IATA MSI / PLESSY Code 32 STD	
		4.5~5.5V DC V1±5
		100~110mA
		30~40mA
		170 L×60 ×95 H
		185
		ABS
		USB
		-200℃ ~50℃
		-40℃ ~70℃
		0~98
		0~70,000
	5mil UPC	40 - 160
	10mil Code93	20mm - 240mm
	15mil EAN13	40 - 250
	20mil code128	40 - 380
	40mil code128	80mm -520mm



OCBS-C006





OCBS-C006





OCBS-C006





