

1D / 2D
M / N OCBS -2013

Feautre

1MP 1MP 1280 * 800
4mil
1D 2D
4mil
ASCII

1
1

1	LED
1	LED
1	LED
1	LED
1	CMOS
1	1280 * 800, 256
1	1300 UPC 40
1	50 20
1	≥400
1	1D UPC-A, UPC-E, UPC-E1, EAN-13, EAN-8, ISBN, Bookland EAN, ISSN, Code 39, Code 39 ASCII, Code 32, Trioptic Code 39, 25, 52, 55, 2 Codabar, NW7, Code 128, UCC / EAN 128, GS1-128, ISBT 128, Code 93, Code 11, USD-8, MSI / Plessey
1	2D PDF417, MicroPDF417, QR, DataMatrix, GS1 Com pos ite
1	Code 39 5mil 50mm 120mm Code 39 10mil 25mm 250mm UPC / EAN 1300 20mm 320mm 7.5mil 63mm 150mm PDF417 660 62mm 145mm
1	±45° @ 0° ±30° @ 0° ±45° @ 0°
1	USB, USB, COM
1	3.3v 5v
1	2.0w 400mA
1	2.5w 450mA
1	5.5V 1A
1	LED
1	-20 +60 -4 144
1	-30°C +70°C -22°F 158°F
1	5-95
1	1.5m 5.0ft
1	IP54
1	



OCBS-2013





OCBS-2013



