

m / n OCBP-012a / b

OCBP

200 MHz 32 RISC
 8 MB SDRAM + 8 MB
 127 5
 300 984'
 203 DPI 300dpi
 Bartender Label Edition

OCBP	OCBP -012A	OCBP -012B.
Resolution	8 / mm 203 dpi	12 / mm 300 dpi
Print Speed	127 mm 5 / s	101.6 mm 4 / s
Print Width	108 mm 4.25"	104 mm 4.09"
Print Length	1178mm 70"	889mm 35"
Print Resolution	20-112mm 0.78-4.4"	
Print Accuracy	0.06 0.254 mm 2.36 10	
Print Area	10 1178 mm 0.39 70"	10 889 mm 0.39 35"
Print Head	127 mm 5" OD	
Print Head Diameter	300 OD 67 mm 1" 40 mm 110 mm 1.6 4.3"	
Print Head Weight	299 mm d x 235 mm w x 198.3 mm h	
Print Head Power	2.55kg.	
Print Head CPU	32 RISC CPU	
Print Head Memory	8MB 8MB SDRAM. SD 4 GB	
Print Head Interface	<ul style="list-style-type: none"> •USB2.0 •RS-232 • 10/100 Mbps • 802.11 B / G / N 	
Print Head Power Supply	AC 100-240V 1A 50-60Hz DC 24V 2.5A 60W	
Print Head LED	1 LED 3	
Print Head Material		
Print Head Weight		
Print Head Dimensions		
Print Head Color		
Print Head Finish		
Print Head Material		
Print Head Weight		
Print Head Dimensions		
Print Head Color		
Print Head Finish		

□□	1D□□□□□□39□□□□93□□□□128UCC□□□□128□□A□B□C□Codabar□□□□2□ean-8□EAN-13□EAN-128□UPC-A□UPC-E□EAN□UPC 2□5□□□□□□□□MS□Plessey□POS TNET□□□□POST 2D□□□□PDF-417□Maxicode□DataMatrix□QR□
□□	Bimap□BMP□PCX□□□□256□□□□
□□□□□□□□	0°□90°□180°□270°
□□□□□□	TSPL.
□□	□□□□5□40°C□25□85□□□□ □□□□-40□60°C□10□90□□□□
□□	①Windows□□□□CD□;②□□□□;③USB□;④□□□□;⑤□□□□□□□□□□;⑥□□□□□□□□□□x 2□1.5"□□□□□□x 2;⑦□□□□;⑧media
□□□□□□	□□□□□□□□□□□□□□□□□□□□□□□□0.06□0.19mm□500000□□□; 0.20□0.25mm□200000□□□□
□□□□	□□□□□□□□□□OD□ 214□□□□8.4"□□□□25.4□□□□1"□□□□□□□□□□□□□□□□□□□□□□□□802.11 B / G / N□□□□□□□□□□RFIDModule□





OCBP-012





OCBP-012





OCBP-012





OCBP-012

