

XXXXXXXXXX

KB887

XX

| | |
|---|--|
| XX | XXXX X CARD XXXXXXXXX |
| XX | 400 |
| XX | 150*110*62 |
| XXXX | -20+60°C |
| XXXXX | 200,000 |
| XXXX | ISO7816XXXXXXXXXXXXGSM 11.11SIMSAM |
| XXXX | 70 |
| XX XX | USBHIDXXXXXXXXRS232 T = 0 T = 1 CPUXXXXXXXXXXXXXXXXXXXX115.200 bps ISO14443 Type A Type BXXXXXXXXXXXXMifare S50 Mifare S70 MF1ICL10 Mifare Pro Mifare desfire Mifare AT88RF020 1102 |
| XXXX XX XXXX XX XX XX XX XX XX XXXX XXXX | T = 0 9600-38400bps T = 1 9600-115200bps XXXXXXXXXXXX 2M LEDXXXXXXXXXXXX LCD 122 * 32,2 8XXXXXXXXXXXX XXXXXXXXXXXX15XXXXXXXXXXXX09XXXXXXXXXXXX3DESXXXXXXXXXXXX 4KXXXXXXXXXXXXIDXXXXXXXXXXXX 1 \ 2 \ 3XXXXXXXXXXXX Windows XP 2003 7 8 10 Unix Linux XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX |