

□□□

32-bit CPU  
 8MB SDRAM,8MB Flash  
 203 dpi □□□  
 152mm(6'')/s □□□□□  
 108mm □□□□  
 25.4-112mm (0.78'-4.56')□□□□□□  
 □□TSPL EPL ZPL DPL□□

□□□

□□□□	
□□	OCBP-018
□□	□□□□□□
□□	USB
□□□	32 □ CPU
□□	8MB □□□8MB SDRAM
□□□□□	30□□
□□	□□□ AC 100V -240V □ 50-60Hz □□□□ DC 24V / 2.5 A
□□□	□□□□□□□□□□□□□□□□
□□□□	□□ 2 □□
□□□□	□□ 2 □□
□□□□□□□□	0° , 90° , 180° , 270°
□□□□	TSPL EPL ZPL DPL
□□□□	
□□□□	□□□
□□□	203 DPI
□□□□	152□□/□
□□□□	□□ 108 □□
□□□□	□□ 1778 □□
□□□□□□	
□□	□□□□□□ Code 39□Code 93□Code 128UCC□Code 128 □□ A□B□C□Codabar□Interleaved 2 of 5□EAN-8□EAN-13□EAN-128□UPC-A□UPC-E□EAN □ UPC 2□ 5) □□□□□MSI□PLESSEY□POS□□□□□□POS□ □□□□□ PDF-417□Maxicode□DataMatrix□□□□
□□	
□□□□	□□□□□□□□□□ □□ □□□
□□□□	26-116mm
□□□□	0.06-0.20mm
□□□□□	□□□□
□□□□	10-1778mm
□□	
□□	185□□□□□ × 85□□□□□ × 85 □□□□□
□□	□□□1.14kg □□□1.3kg
□□□	220*180*130mm
12 □ 1 □	560*460*285mm/17.1kg
□□	
□□□□□□□	0 to 4 5 °C , 10%~80% □□□
□□□□□□□	-20 □ 60□□□□ 10%~90% □□□

