

## 2

### M / N OCBP - 201

□□□

USB □ USB + □□□□□□;

□□□□□□□□;

□□□□□□□□;

□□□□□□□□□□□□;

□□ TSPL □ ESC / POS □□;

□□□□□□□□□□□□□□□□

□□□

□□□□	□□□□
□□□	203DPI
□□	TSPL □ ESC / POS
□□□□	□□□□□□□□□□□□□□ □□□□ HEX □ 1F 1B 1F 02 20 n 0D 0A □ n = 31 / 30.default n = 30 □
□□□□	48mm
□□□□□□	MAX □ 101 □□/□; MIN □ 50.8 □□/ s □
□□	DRAM □ 256kb FLASH □ 576kb
□□□□□□	□□□□□
□□□□□□	□□□□□
□□	USB □ USB + □□
□□□□□□□□	□□□□□□□□
□□	CODE128 □ EAN128 □ ITF □ CODE39 □ CODE93 □ EAN13 □ EAN13 + 2 □ EAN13 + 5 □ EAN8 □ EAN8 + 2 □ EAN8 + 5 □ CODABAR □ POS TNET □ UPC-A □ UPCA + 2 □ UPCA + 5 □ UPC-E □ UPCE + 2 □ UPC-E + 5 □ C POS T □ MSI □ MSIC □ PLESSEY □ ITF14 □ EAN14 Qrcode □ DM □□□ PDF417
□□□□□□	□ 0° □ 90° □ 270° □ 360° □□□□□□□□ 1 □ 10 □; 0° □ 90° □ 270° □ 360° □□
□□	□□ PCX □ BMP □□□□□□□□□□ FLASH
□□□□	□□□□□□□□□□□□□□
□□□□	20 □□□□ 60 □□
□□□□	□□ 80 □□
□□□	□□ 25 □□
□□□□	□□
□□□□	DC12V □ 3A
□□□□	5 ~ 45 °C □□□□□□ 20-80 □□□□□□

□□	-40□55°C□≤93□RH□40°C□
□□	





OCBP-201





OCBP-201





OCBP-201





OCBP-201





OCBP-201





OCBP-201







OCBP-201





OCBP-201

