

360° 2D

M / N OCBS -2012

□□□

1. □□□□□□□□
2. □□□□□□□□□□
3. □□□□□□1D□2D□□□□□□□□□□
4. □□□□□□□□□□□□□□□□
5. 5mil□□□□□□□□□□□□□□□□
6. □□□□□□□□□□□□
7. □□□□□□□□

□□□

□□□□		
□□□		640 * 480□256□
□□		□□□□□□617 □□±10□□□
□□		0□100,000□□□
□□□□		□ 360°\□□ ±60°\□□ ±65°
□□□□		300□□/□
□□□	2D	DataMatrix□Matrix 2 of 5□MaxiCode□MicroPDF417□MSI Code□PDF417□QR code□Standard 2 of 5□Telepen□TLC 39□
	□□	□□□□Pos□□□□□□□□□□BPO□□□□□Pos□□□Codabar□Codablock□□□□11□□□39□□□93□□□128 / EAN128□□□□□Pos□□□EAN.UCC Com pos ite□5□□2□□□□Pos t□ Planet□Plessey Code□Pos tnet□RSS□UPC / EAN□
□□		≥500□ □□□□□□□□
□		360°
□□		65°
□□		75°
□□□□		
□□		RS232 / USB/ USB□□COM
□□		□□5 V±5□
□□		190 mA□□□□□
□□		1.5□
□□		1□65□G
□□□		170□□x 60□□x95□□
□□□□		

工作温度	-5℃~65℃
存储温度	-20℃~70℃
湿度	5%-95%RH
寿命	≥100,000次扫描





OCBS-2012





OCBS-2012





OCBS-2012





OCBS-2012

