

1D / 2D

OCBS -2015

-

300 DPM OCR

-

-

40 100

-

1.8 IP42

-

-

USB

| | | | |
|--|------|---|------|
| | | | |
| | CMOS | * | ≥300 |

| | | | |
|-------|--|---|---------------|
| 尺寸 | 1280 * 960 | 重量* | 2 m / 箱 |
| 光源 | LED / LED | 视角 | 40.5° / 30.4° |
| 波长 | 650nm | 寿命* | ≥25万 |
| 功能 | 2D | PDF417 QR | |
| | 1D | EAN-13 EAN-8 UPC-A UPC-E ISSN ISBN Codabar Code 128 Code93 ITF-6 ITF-14 5 2 5 2 5 2 5 Matrix2 GS1 MSI-Plessey Plessey | |
| 规格 | 分辨率 | 2015-1 | 2015-2 |
| | EAN-13 1300 | 25 155 | 40 410 |
| | 39 500 | 50 100 | 110 250 |
| | PDF 417 670 | 40 105 | 115 190 |
| | 1000 | 40 110 | 100 250 |
| | 1500 | 35 155 | 70 280 |
| 温度 | 工作 | ±50° | |
| | 存储 | 360° | |
| | 运输 | ±50° | |
| 接口 | | | |
| 接口 | RS-232 USB PS / 2 | 接口 | LED |
| 尺寸 | 166 * 107 * 71 mm | 电压 | 5 VDC ±5% |
| 功率 | 208 | 功耗 | 1251 mW |
| 5 VDC | 266 mA | 重量 | 109g |
| 环境 | | | |
| 温度 | -20°C ~ 50°C | 湿度 | ±16 kV ±8 kV |
| 温度 | -40°C ~ +70°C | 防护 | 1.8m |
| 防护 | 5 95 | 防护 | IP42 |
| 认证 | FCC Part15 B CE EMC B | | |
| 接口 | | | |
| 接口 | USB | USB | |
| | RS-232 | RS-232 | |
| | PS / 2 | PS / 2 | |
| 电源 | 5V RS232 DC 5V 1.5A AC100 240V 50 60Hz | | |
| 其他 | | | |
| 重量 | | | |
| 重量 | | | |



OCBS-2015





OCBS-2015





OCBS-2015





OCBS-2015





OCBS-2015

