



□□	2D	PDF417□QR□□□□□□□□□□	
	□□	EAN-13□EAN-8□UPC-A□UPC-E□ISSN□ISBN□Codabar□Code 128□Code93□ITF-6□ ITF-14□5□□□□2□5□□□□2□5□□□□2□5□□□□□2□5□□□□□□□□□□ Matrix2□GS1□□□□□□□□ 39□□□□11□MSI-Plessey□Plessey□	
□□□□*	□□□□	2015-1	2015-2
	EAN-13□1300□□	25□□□□155□□	40□□□□410□□
	□□39□500□□	50□□□□100□□	110□□□□250□□
	PDF 417□670□□	40□□□□105□□	115□□□□190□□
	□□□□□1000□□	40□□□□110□□	100□□□□250□□
	□□□□□1500□□	35□□□□155□□	70□□□□280□□
□□□□□□*	□□	±50°	
	□□	360°	
	□□	±50°	
□□			
□□	RS-232□USB□PS / 2	□□□□	□□□□LED□□□□□□□□
□□	166□□□* 107□□□* 71□□□ mm	□□	5 VDC±5□
□□	208□	□□□□ □□	1251 mW□□□□□□
□□@ 5 VDC	□□□□266 mA□□□□□□	□□□□	109□□
□□□□			
□□□□	-20°C□50°C	□□□□	±16 kV□□□□□□□□±8 kV□□□□□□□□
□□□□	-40°C□+ 70°C	□□	1.8m
□□	5□□95□□□□□□□□	IP□□	IP42
□□□□ FCC Part15 B□□CE EMC B□			
□□			
□□	USB	USB□□□□□□□□□□□□	
	RS-232	RS-232□□□□□□□□□□□□□□	
	PS / 2	PS / 2□□□□□□□□□□□□□□	
□□□□	5V□□□□□□□□□□□□RS232□□□□ □□□□DC 5V□1.5A□□□□□□AC100□240V□50□60Hz		
□□			
□□□□□□	□□□□		
□□□□□□	□□□□		



OCBS-2015





OCBS-2015





OCBS-2015





OCBS-2015





OCBS-2015





OCBS-2015







OCBS-2015

