

□□□□□□/□□□□□□□□

□□□□□□(OCBS-2017)

□□□□

□□□□□□□□

□□□□□□

4 mil □□□□□□□□

□□□□□□□□□□

□□□□□□ 1D □ 2D □□□□□□□□□□

□□□□□□□□□□□□□□□□

□□□

□□	USB; USB□□COM□RS232
□□□□	Linux□Android□Windows XP□7□8□10□MAC
□□□	CMOS□□□
□□	□□LED(□□)+□□LED(□□)
□□□	32□ARM□□□+DSP
□□□	≥4mil□PCS90%,CODE 39□
□□□	1/5 □□
□□□□	25□□/□
□□□□	□□
□□□□	□□□□□□□□□□□□
□□□□	□□□□□□□□LED□
□□□□□□	≥25%
□□	ABS+PC
□□	□□ 5V ±5%
□□□□	375mW□□□□□□226mW□□□□□□750mW□□□□□□ □□□□□□□□
□□	289g±5g
□□□□	□*□*□□180 * 115 * 85□□□□mm□
□□□□□□	60*45*38.5 cm 50□/□, NW.=14.45kg , GW.=16.15kg
□□	□□□
□□□□	□□
□□□□	●Code25-Interleaved ●Code25-Standard ●Code25-Matri ●Code39-Regular ●Code39-FullASCII ●Code32 ●Code93-Regular ●Code93-FullASCII ●Code128 ●EAN/GSL/UCC-128Auto ●Codabar ●MSI ●EAN/JAN-13 ●UPC-A ●JAN-8 ●UPCE
□□□□	□□
□□□□	● □□□ ● □□□□ ● PDF417
□□□□	Roll360°, Pitch30°, Yaw45°
□□□□	Code39 4.17mil□15 □□□□4cm - 8cm
□□□□	Code128 4.17mil□16□□□□7cm - 15cm
□□□□	□□□□ 1083 □□8 □□□□3cm - 9cm
□□□□	□□□ 20mil□8 □□□□1cm - 19cm

IP42	
0 ~ 50°C / 32 ~ 122°F	
0 ~ 50°C / 32 ~ 122°F	
20% ~ 85%	
20% ~ 85%	
ESD	15KV
1.5m	



OCBS-2017





OCBS-2017





OCBS-2017





OCBS-2017





OCBS-2017

