

1D / 2D

OCBS -2018

Feautre

1MP * 1MP * 1280 * 800

1D 2D

4mil

	USB; RS232
	Linux Android Windows XP 7 8 10 MAC
	; ; ; ; ; ; ;
	CMOS
	LED + LED
	32 ARM MCU + DSP
	Code39 35cm /
	400
	1/5
	LED
	20
	ABS + PC
	5V ± 5
	375mW; 226mW; 750mW
	145.0g ± 5g
	* * 164.5 * 91.5 * 68.0 mm
	+

□□□□	□□	●□□25□□●□□25□□-□□25□□
		●□□39-□□●□□39-□ASCII●□□32
		●□□93-□□●□□93-□ASCII●□□128
		●EAN / GSL / UCC-128Auto●Codabar●MSI
		●EAN / JAN-13●UPC-A●JAN-8●Code11●UPCE0
	2D	●MICRO QR●□□□□●QR ●AZTEC●PDF417
□□□□	□□360°□□□30°□□□45°	
□□□□	Code39 4.17mil□15□□□□6cm-12cm	
	Code128 4.17mil□16□□□□7cm-10cm	
	□□□□10.83mil□8 bytes□□5cm-16cm	
	□QR 1083mil□8 bytes□□7cm-12cm	
□□□□		
IP□□	IP52	
□□□□	0□50°C/ 32□122°F	
□□□□	0□50°C/ 32□122°F	
□□□□	20□□85□□□□□□□□	
□□□□	20□□85□□□□□□□□	
□□□□	15KV□□	
□□□□	□1.5m□□□□□□	



OCBS-2018





OCBS-2018





OCBS-2018





OCBS-2018





OCBS-2018





OCBS-2018

