

OCBS -2019 1D 2D QR

OCBS -2019



Feautre

n

n

n 4 mil

n

n 1D 2D

n

	USB; RS232
	Linux Android Windows XP 7 8 10 MAC
	; ; ; ; ;
	CMOS
	LED + LED
	32 ARM MCU + DSP
	Code39 35cm /

□□□	400□
□□□	1/5□□
□□□□	□□
□□□□	□□□□□□□□□□□□
□□□□	□□□□□□□□LED□
□□□□□	20□
□□	ABS +PC
□□	□□5V±5□
□□□□	375mW□□□□; 226mW□□□□; 750mW□□□□
	□□□□□□□□
□□	289□±5□
□□□□	□*□*□□180 * 115 * 85□□□□mm□
□□□□	60 * 45 * 38.5□□50□/□□□□□□ = 14.45kg□□□□ = 16.15kg
□□	□□+□□
□□□□	□□
	<ul style="list-style-type: none"> ●□□25□□●□□25□□-□□25□□ ●□□39-□□●□□39-□ASCII●□□32 ●□□93-□□●□□93-□ASCII●□□128 ●EAN / GSL / UCC-128Auto●Codabar●MSI ●EAN / JAN-13●UPC-A●JAN-8●Code11●UPCE0
	2D
	<ul style="list-style-type: none"> ●MICRO QR●□□□□●QR ●AZTEC●PDF417
□□□□	□□360°□□□30°□□□45°
□□□□	Code39 4.17mil□15□□□□6cm-12cm
	Code128 4.17mil□16□□□□7cm-10cm
	□□□□10.83mil□8 bytes□□5cm-16cm
	□QR 1083mil□8 bytes□□7cm-12cm
□□□□	
IP□□	IP52
□□□□	0□50°C/ 32□122°F
□□□□	0□50°C/ 32□122°F
□□□□	20□□85□□□□□□□□

□□□□	20□□85□□□□□□
□□□□	15KV□□
□□□	□1.5m□□□□□□□□



OCBS-2019





OCBS-2019





OCBS-2019





OCBS-2019





OCBS-2019





OCBS-2019

