

OCBS-F2100

- ñ
- ñ
- ñ 1D
- ñ
- ñ 4mil
- ñ

OCBS

OCBS	LED
OCBS	LED
OCBS	CMOS
OCBS	640 * 480,256
OCBS	13mil UPC 40cm / s
OCBS	50; 20
OCBS	≥4mil
OCBS	1D
OCBS	2D
OCBS	Composite
OCBS	Code 39 5mil 50 120
OCBS	Code 39 10mil 25 250
OCBS	UPC / EAN 13mil 20 320
OCBS	7.5mil 63 150
OCBS	PDF417 6.6mil 62 145
OCBS	±45° @ 0° 0°
OCBS	±30° @ 0° 0°
OCBS	±45° @ 0° 0°

OCBS	USB	USB COM
OCBS	3.3v	5v DC
OCBS	2.0w	400mA
OCBS	2.5w	450mA
DC	5.5V	1A
LED		I
EMC	FCC	15 IEC60825-1 EN55022 B

OCBS	-20	+60	-4	144
OCBS	-30°C	+ 70°C	-22°C	F 158
OCBS	5	- 95		
OCBS	1.5	5.0		
OCBS				

PIN NO			
1	---	NC	
2		VCC	3.3V
3		GND	
4		RX	
		TX	

□
7
8
9
10
11
12

□□
□□

□□
□□

□□

D-
d +
NC
BEEPER
DLED
NC
TRIG

USB□□□□
USB□□□□
□□
□□□□□□
□□□□□□
□□
□□□□□□

□□□

