

□□□

- l. 200MM/S □□□□
- m. 10-40cm□□□
- n. □□□□□□□□
- o. □□□□□ 1.5m □□□□
- p. □□□□□□□□□□□□

□□□

□□□	
□□	OCBS - L017
□□	ABS+PVC+PC
□	□□□□
□□	USB
□□□□	□□□□□□□
□□□□	50m A□□□□□40m A□□□□□100m A□□□□
□□	□□ 5V±5%
□□□□	20□□
ESD□□	15KV□□□□
□□□	□□□□□ 1.5m □□□□
□□	
□□□□	□□ 200 □□□
□□□□	2—9cm□0.1mm□□□3—30cm □ 0.3mm□□
□□□□	□□ 0.1mm(4mils)
□□□□□	25% ≥
□□□□	10- 4 00mm Roll 60°, Pitch45°
□□	□□ □□650nm
□□□□	1D □UPC-A , UPC-E , EAN-8 , EAN-13 , Code 128 , Code 39 , Code 93 , Interleaved 2 of 5 , Matrix 2 of 5 , Industrial 2 of 5 , Standard 2 of 5(IATA25) , Codabar □NW-7 □□
□□□	
□□□□	150mm * 70mm * 95mm
□□	
□□□□□□□	0 to 4 5 °C , 10%~80% □□□
□□□□□□□	-20 □ 60□□□ □10%~90% □□□









