

OCBS-LA01

ModelNo OCBS-LA01

Spec

- Wavelength: 650-670nm
- Power: 100mW SPS
- Beam Diameter: 8mm
- Range: 1 / 3,000,000
- Spot Size: 2.5~600mm
- Accuracy: ±0.1mm
- Resolution: 4mm PCS 0.9
- Resolution: 20mm @ 650nm
- Angle: 45° / 60°
- Barcode: UPC / EAN, UCC / EAN128, 39 ASCII, 39 trioptic, 128 ASCII, codabar, 2 of 5, 5 of 9, MSI, 11 ATA, RSS, 2 of 5 ...
- Interface: PS2, RS232, USB
- Voltage: DC + 5V +/- 5%
- Current: 100mA, 110mA
- Power Consumption: < 30mA
- Interface: RS232
- Dimensions: L200mm x W72mm x H58.5mm
- Weight: 480g
- Material: Aluminum
- Color: Silver

Table

OCBS-LA01	
Wavelength	650-670nm
Power	100mW SPS
Beam Diameter	8mm
Range	1 / 3,000,000
Spot Size	2.5~600mm
Accuracy	±0.1mm
Resolution	4mm PCS 0.9
Resolution	20mm @ 650nm
Angle	45° / 60°
Barcode	UPC / EAN, UCC / EAN128, 39 ASCII, 39 trioptic, 128 ASCII, codabar, 2 of 5, 5 of 9, MSI, 11 ATA, RSS, 2 of 5 ...
Interface	
Interface	PS2, RS232, USB
Voltage	DC + 5V +/- 5%
Current	100mA, 110mA
Power Consumption	< 30mA
Interface	RS232
Dimensions	L200mm x W72mm x H58.5mm
Weight	480g
Material	Aluminum
Color	Silver



OCBS-LA01



www.ocominc.com

