

OCBS -LA06

OCBS-LA06



特性

;

;

;

KBW RS232 USB;

;

規格

波長	
波長	650-670nm
視野	200
距離	2.5~600mm 100 UPC / EAN
解像度	
線幅	PCS 0.9 0.10mm 4mil
読み取り速度	20 @ 650nm
読み取りコード	UPC / EAN UPC / EAN UCC / EAN128 39 39 ASCII 39 trioptic 128 128 ASCII codabar 2 of 5 2 of 5 93 MSI 11 ATA RSS 2 of 5 ...
インターフェース	
インターフェース	PS2 RS232 USB
電源	DC + 5V +/- 5
消費電力	100
電流	< 40mA

□□□□	□□□□□□□□RS232□□□
□□□□	□□45°□□60°
□□□□□	L165.42mm X W69.72mm X H89.67mm
□□□	140□□□□□□□
□□	□
□□□	□□□□□□
□□□□	
□□□□□	0°C□50°C
□□□□□	-40°C~70°C
□□□	□□□□5~95□□□□□
□□□□□	□□+/- 15KV□□□□□+/- 8KV□□□□
□□□□□	□□□□□□1.5□□□□□□□
□□□	
EMI / RFI□	FCC A□□CE
□□□□□	CDRH 2□□□□□



OCBS-LA06





OCBS-LA06



