

2D

M / N OCBS -T209

300,000 Ex pos URE

4

LED

1D 2D

Microsoft Windows / Linux / Android / IOS / MacOS

LED	LED
640 * 480	
0.102mm / 4mils.	
≥15	
2M /	
0-360°; ±60°; ±60°	
1D GS1 DataBar™ 2D AZTEC; maxicode; MicroQR GS1 Databar; GS1 Databar; GS1 DataBar GS1 DataBar COM pos ITE; micropdf417; PDF417	
LED /	
	<ul style="list-style-type: none">5MIL. 128.0mm-70mm.5MIL. 13.0mm-70mm.4mil. 13.0mm-240mm.5MIL. PDF417 0mm-60mm.10mil. PDF417 0mm-170mm.15mil. PDF417 0mm-270mm.20Mil. DM. 0mm-80mm.
L * W * H	96 * 105.55 * 157.06mm
	278G.
	1.8M.
	< 300 mA < 210 mA
	5 VDC +/- 10% / 500mA
ESD	8 kv.
	1.2M / 4.0FT

□□	□□□0□40°C □□/□□□-40□70°C
□□□□□□□	5 - 95□
□□□	0 -100,000□□□
□□	
□□	RS-232; USB HID; USB COM; HID POS□□□□□□□□□□



















