

OCBS T214

- T214)

1. 1

1. 1
2. 2/3
3. 1
4. 1

2

OCBS	OCBS-T2 14
USB	USB
5V	5V
380	380
24 0	24 0
190	190
8 G r.m.s. 10 500 Hz 2 3	8 G r.m.s. 10 500 Hz 2 3
CMOS	CMOS
LED	LED
44 ° (), 34 °	44 ° (), 34 °
> 0.4m/S	> 0.4m/S
	±6 5 °@ 0°Roll 0° Skew 360°@ 0° 0° ± 6 5°@ 0°Roll 0° Pitch
20%	20%
0-100,000	0-100,000
	Code39(5mil):0-120mm, Code39(13mil):0mm-240mm QR(20mil):0mm-210mm QR(QR 30*30mm):40mm-650mm QR(QR 23mm*23mm):20mm-550mm
	Code128 / 128, EAN .UCC 2 of 5 ,RSS,Postnet, 39 , 93 , 11 , Standard 2 of 5 UPC/EAN 2D PDF417 Matrix 2 of 5 MicroPDF417 MaxiCode Codablock Aztec TLC 39 DataMatrix
437 g	437 g
151 *1 42 * 84 mm	151 *1 42 * 84 mm
245X165X105mm /700g	245X165X105mm /700g
15 1	525X430X360mm/12kg
0 45 10%~80%	0 45 10%~80%
-20 60 10%~90%	-20 60 10%~90%











