

□□□□□□□□

□M/N□OCBS-T216□

□□□



□□□□□□4mils□

□□ LED □□□□□□□□

□□□□□□□□□□□□

□□□□□□□□□□

□□□□10%□□□□□□□□□□

□□□□□□□□□□OCR□

□□□

品牌	
型号	OCBS-T216
接口	USB
分辨率	USB RS232
传输距离	1.8M
光源	LED
功率	500mA/1A
功耗	150mA 待机 530mA 工作
操作系统	Windows/Linux/Android/IOS/MacOS
扫描速度	1.5m/4.0 秒
品牌	
传感器	CMOS 1280*800
分辨率	1,000,000
精度	≥4mil/0.1mm PCS90%, 39
扫描范围	0mm~500mm
扫描速度	100/秒
光源	LED
接口	USB
扫描角度	±360° 俯仰: ±70° 偏航: ±65° (CODE39, 10mil/0.25mm, PCS90%)
识别率	≥20%
接口	USB
扫描范围	4mil 39 10mm—70mm 10mil 39 0mm—190mm 13mil UPC/EAN 0mm—250mm 20mil 10mm—200mm ETC..... 支持多种条码格式
支持的条码	1D UPC-A, UPC-E, EAN-8, EAN-13, ISBN, ISSN, 128, GS1-128, ICBT, 39, 32, 93, 11, Codabar(NW-7), Interleaved 2 of 5, Matrix 2 of 5, 2 of 5 (Straight 2 of 5), 2 of 5 (IATA 2 of 5), NEC 2 of 5, MSI 2D: QR Code, Micro QR Code, Data Matrix, PDF417, Micro PDF 417, MaxiCode, Aztec, HanXin Code, Pharma Code(One-Track), Codablock A, Codablock F, Dot Code GS1 Databar, GS1 TLC 39, OCR, 2 of 5, USPS, Planet Code, Postnet Code, UPU 4-State, KIX Code
品牌	
重量	700g
尺寸	220*180*110mm
品牌	
工作温度	0~45°C 10%~80% RH
存储温度	-20~60°C 10%~90% RH











Model: OCBS-T216

Input: DC5V/0.5A



OCBS-T216334180004

NOTE: DON'T STARE AT LED LIGHTS WHILE

OPERATING.



MADE IN CHINA









**Aocom** 2D Barcode Scanner  
Model: OCBS-T216 Color: Black  
Interface: USB  
Power Input: 5V 1A CE FC  
OCBST216233410006  
MADE IN CHINA