

OCBS-T218

# OCBS-T218

OCBS

OCBS-T218

400万像素

640\*480 CMOS

OCBS-T218

OCBS

OCBS-T218	OCBS-T2 18
USB	USB
5V	5V
315	315
320	320
235	235
120	120
CMOS 640*480	CMOS 640*480
(Timer) LED, (Illumination) LED	(Timer) LED, (Illumination) LED
39° (x)29°	39° (x)29°
>= 4mil	>= 4mil
±6.5°@0°Roll 0° Skew 360°@0° 0° ±6.5°@0°Roll 0° Pitch	±6.5°@0°Roll 0° Skew 360°@0° 0° ±6.5°@0°Roll 0° Pitch
20%	20%
0-100,000	0-100,000
39(5mil):0-70mm, Code39(13mil):0mm-170mm QR(20mil):0mm-110mm, QR(30mm*30mm):0mm-300mm	39(5mil):0-70mm, Code39(13mil):0mm-170mm QR(20mil):0mm-110mm, QR(30mm*30mm):0mm-300mm
39, 32 (PARAF), Interleaved 2 of 5, NEC 2 of 5, Code 93, StraiGht 2 of 5 Industrial, Straight 2 of 5 IATA, Matrix 2 of 5, Code 11, Code 128, GS1-128, UPC-A, UPC-E, EAN/JAN-8, EAN/JAN-13, MSI, GS1 DataBar Omnidirectional, GS1 DataBar Limited, GS1 DataBar Expanded, (2 of 5), T Code, A, F, PDF417, MicroPDF417, GS1 C, Data Matrix, MaxiCode, Aztec,	39, 32 (PARAF), Interleaved 2 of 5, NEC 2 of 5, Code 93, StraiGht 2 of 5 Industrial, Straight 2 of 5 IATA, Matrix 2 of 5, Code 11, Code 128, GS1-128, UPC-A, UPC-E, EAN/JAN-8, EAN/JAN-13, MSI, GS1 DataBar Omnidirectional, GS1 DataBar Limited, GS1 DataBar Expanded, (2 of 5), T Code, A, F, PDF417, MicroPDF417, GS1 C, Data Matrix, MaxiCode, Aztec,
Codabar, Code39, Interleaved2of5, NEC2of5, Code93, Code128, GS1-128, UPC-A, UPC-E0, EAN/JAN-13, EAN/JAN-8, GS1-DataBar, PDF417, QR, DM, Aztec	Codabar, Code39, Interleaved2of5, NEC2of5, Code93, Code128, GS1-128, UPC-A, UPC-E0, EAN/JAN-13, EAN/JAN-8, GS1-DataBar, PDF417, QR, DM, Aztec
249 g	249 g
140.2* 84* 90.1 mm	140.2* 84* 90.1 mm
45%~80%	45%~80%
-20 60 10%~90%	-20 60 10%~90%









