



- 218)

1.1

1. 100000000000
2. 4000000000
3. 640 * 480 0000
4. 00000000

1.2

00	OCBS-T2 18
00	USB
0000	5V
0000	315mA
000	320 235mm
0000	120 000000
000	CMOS 640*480
00	(Aimer) LED, (Illumination) LED
00	39° ()x29° 000
000	>= 4mil
0000	±6.5°@0°Roll 0° Skew 360°@0° 0° ±6.5°@0°Roll 0° Pitch
0000	0000 20%
000000	0-100,000
0000	39(5mil):0-70mm, Code39(13mil):0mm-170mm QR(20mil):0mm-110mm, QR(30mm*30mm):0mm-300mm
0000	000 000 , 39 , 32 (PARAF) , Interleaved 2 of 5, NEC 2 of 5, Code 93, StraiGht 2 of 5 Industrial, Straight 2 of 5 IATA, Matrix 2 of 5, Code 11, Code 128, GS1-128, UPC-A, UPC-E, EAN/JAN-8, EAN/JAN-13, MSI, GS1 DataBar Omnidirectional, GS1 DataBar Limited, GS1 DataBar Expanded, (2 of 5), 000 T Code , 000 - A , 000-F, PDF417 , MicroPDF417 , GS1 C 0000 , 000 , Data Matrix, MaxiCode, Aztec, 000
0000	Codabar, Code39, Interleaved2of5, NEC2of5, Code93, Code128, GS1-128, UPC-A, UPC-E0, EAN/JAN-13, EAN/JAN-8, GS1-DataBar, PDF417, QR, DM, Aztec
00	:249 g
00	140.2* 84* 90.1 mm
00	122X165X105mm /343g
30100	525X430X360mm, 11.8kg
0000	04500010%~80%
0000	-20 60 00010%~90%











