



- 218 )

1. 1

1. 1
2. 400
3. 640 \* 480
4. 1

2. 2

OCBS-T2 18	
USB	
5V	
315	
320 235m	
120	
CMOS 640*480	
(Aimer) LED, (Illumination) LED	
39 ° (x)29 °	
>= 4mil	
±6.5° @ 0° Roll 0° Skew 360° @ 0° 0° ± 6.5° @ 0° Roll 0° Pitch	
20%	
0-100,000	
39(5mil):0-70mm, Code39(13mil):0mm-170mm QR(20mil):0mm-110mm, (QR 30mm*30mm):0mm-300mm	
39, 32 (PARAF), Interleaved 2 of 5, NEC 2 of 5, Code 93, StraiGht 2 of 5 Industrial, Straight 2 of 5 IATA, Matrix 2 of 5, Code 11, Code 128, GS1-128, UPC-A, UPC-E, EAN/JAN-8, EAN/JAN-13, MSI, GS1 DataBar Omnidirectional, GS1 DataBar Limited, GS1 DataBar Expanded, (2 of 5), T Code, A, F, PDF417, MicroPDF417, GS1 C, , Data Matrix, MaxiCode, Aztec, Codabar, Code39, Interleaved2of5, NEC2of5, Code93, Code128, GS1-128, UPC-A, UPC-E0, EAN/JAN-13, EAN/JAN-8, GS1-DataBar, PDF417, QR, DM, Aztec	
:249 g	
140.2* 84* 90.1 mm	
122X165X105mm /343g	
301 525X430X360mm, 11.8kg	
04510%~80%	
-20 60 10%~90%	











