



- 00218

000

1. 000000000000
2. 4000000000
3. 640 * 480 CMOS
4. 0000000000

00

00	OCBS-T2 18
00	USB
0000	5V
0000	315
000	320 235mA
0000	120
000	CMOS 640*480
00	()LED()LED
00	39 ° ()x29 °
00	>= 4mil
0000	±6.5°@ 0°0° 360°@ 0° 0° ± 6.5°@ 0°0°
0000	20%
000000	0-100,000
0000	39(5mil):0-70mm,39(13mil):0mm-170mm QR(20mil):0mm-110mm,(QR 30mm*30mm):0mm-300mm
0000	00 00 , 39 , 32 (PARAF) , Interleaved 2 of 5 NEC 2 of 5 93 Straight 2 of 5 Industrial Straight 2 of 5 IATA Matrix 2 of 5 Code 11 Code 128 GS1-128 UPC-A UPC-E EAN/JAN-8 EAN/JAN-13 MSI GS1 DataBar GS1 DataBar Limited GS1 DataBar Expanded 2 of 5 T Code , A , F, PDF417 , PDF417 , GS1 C , , Data Matrix, MaxiCode, Aztec, HANXIN
0000	Codabar Code39 Interleaved2of5 NEC2of5 Code93 Code128 GS 1-128 UPC-A UPC-E EAN/JAN-13 EAN/JAN-8 GS1- DataBar PDF417 QR DM Aztec
00	:249 g
00	140.2* 84* 90.1 mm
00	122X165X105/343
30 1	525X430X360mm,11.8kg
0000&00	045°C10%80%
000000	-206010%~90%











