

□□□□ /□□ □□□□

- W2□□□□1□□□□□□□□□□7)

□□□

1. □□□□□□□□
2. □□□□□□
3. 4□□□□□□□□□□□□□□□□ □□ □□□□□□□□
4. 2.4G□□□□US□□□□□□□□
5. 1200□□□□□□□□□□□□12□□
6. 16MB□□□□□□□□100000□□□□
7. □□□□□□□□□□□□
8. □□□□□□□□□□□□□□□□
9. □□□□ □□□□□□□□□□□□ □□

□□

□□	- W217
□□	B □□
□□	ABSPC
□□□□□□	IP 42
□□□	3□2 □ ARM □□□ DSP
W □□□	100□2.4G□□
□□□□	□□ 5□□□□V ±5%
□□	USB
□□	1200mAh
□□□□	375mW□□□□□226mW□□□□□750mW□□□□
□□□□	□□□□□□□□(LED)
□□□□	□□□□□□□□□□□□
□□	16MB
□□□□	12□□
□□□□	4□□□
□□□□	15KV□□□□
□□□□	□□□□□1.5m□□□□
□□□□	Linux□Android,Windows XP,7,8,10,MAC
□□	□□OS□□□□
□□	□□LED□□□□□□LED□□□□
□□□□	□□
□□□□□□	≥2 5 %
□□□□	≥ 4 □□□PCS90%,CODE 39□
□□□□	25□□/□
□□□□	Roll360°,Pitch30°,Yaw45°
□□□□	Code39 417□□15□□□□ 4 □□ -8 □□ Code128 4.17□□(16 bytes):7□□ - 1 5 □□ □□□□ 1083 □□8 □□□□ 3 □□ -9 □□ □□□□ 20 □□ □8 □□□□ 1 □□ - 1 9 □□
□□□□	1/5 □□
□□□□	□□□□ Code25-□□ , Code25-□□ , Code25□□ x, Code39-□□ , Code39-FullASCII□ , Code32 , Code128 , EAN/GSL/UCC-128□□ , □□□ , □□ , EAN/JAN-13 , UPC-A , 1□8□ , □□□□ □□ □□□□ □□□□ , □□□□ , PDF417
□□	□□□□ 289 g

20 1 □	455* 415* 210 □□/ 6.65 □□
□□	
□□□□	0□45□□□□10%~80% □□□
□□□□	-20 □ 60 □□□□10%~90% □□□

















