

2.4GHz 2D

OCBS -W232



□□□

□□□□□□□□□□

32□□□□□□□□□□□□□□

□□□□2.4GHz□□□□□□□□

□□□□2.4GHz□□□□□□□□□□100m;

□□□□□□□□□□□□□□15m□

□□□□□□□□□□□□□□□□

□□□□□□□□□□□□□□□□

□□□

□□□□	
□□□□	□□□□
□□	16MB
□□□□□	168mm * 72mm * 93mm
□□□□□	130□□* 45□□* 129□□
□□	ABS + TPR /□□□
□□	370□
□□□□	□□□□□□□□□□
□□□	LED□□□□□
□□□	□□□□□□□
□□□□	
□□□□□	10-450mm□□□□0.9□□0.25□
□□□□	300□□□/□
□□□□	0.10-0.825□□
□□□	1 /□500□□

支持的条码格式	UPC / EAN / EAN128 / Code39 / Code 39 ASCII / Trioptic Code 39 / Code 128 / Code 128 Full ASCII / Codabar / Code 25 / Code 25 / Code 93 / MSI / RSS / MSI / Plessey / UCC / EAN 128 / GS1 DataBar / RSS / QR / PDF417 / DATAMATRIX
电压 / 容量	3.7V / 750mAh
充电电压	3.0V
充电时间	30分钟
充电电流	95mA; 25mA
扫描角度	60°; 45°
频率	433MHz
接口	USB
工作温度	-10°C至45°C / -40°C至60°C
湿度	5% - 90%
扫描距离	1.5m
扫描速度	0 - 100,000 / 秒
静电防护	±12KV / ±6KV
认证	CE / FCC / RoHS

**Aocom**<sup>®</sup>  
All your side

OCBS-W232

ISO FCC CE RoHS



# OCBS-W232





# OCBS-W232





OCBS-W232





OCBS-W232





OCBS-W232









OCBS-W232





OCBS-W232



## Relevant documents:

[OCBS-W232 user manual](#)