

OCBS-W234

M / N OCBS-W234

OCOM 2.4GHz M / N OCBS-W234 OCBS-W234 1D 1D QR 12

2.4GHz

80

100

190mAh 40,000

12

1000

| | |
|--|---|
| | |
| | ABS + PC + TPU |
| | 5V±5 |
| | 190mAh |
| | 3.7V 2000mAH 18650 |
| | 6.5 |
| | > 12 |
| | 170±5 |
| | |
| | 2.4GHz |
| | 50-80M |
| | LED+LED |
| | 2M 40000 |
| | Codabar Code11 Code39 / Code93 UPC / EAN Code128 / EAN128 InterLeaved2of5 Matrix2of5 MSI CODE Standard2of5 QR PDF417 |
| | Code39 5mil QR 8.7mil PCS45 |
| | 5MIL CODE39 5--12 CM 15MIL CODE39 4--25 CM 10MIL CODE93 4--21 CM 15MIL UPC / EAN 4--25 CM 20MIL QR 4--25 CM |

| | |
|------|---|
| 扫描速度 | 400times /秒 |
| 分辨率 | 1/5英寸 |
| 扫描距离 | 0.05-0.5米 |
| 扫描面积 | 5 *5cm ² - 30 *30cm ² |
| 光源 | 红外LED |
| 扫描角度 | ±35° |
| 扫描范围 | 0-360° 俯仰±65° 偏航±60° |
| 防护等级 | |
| IP等级 | ≥IP54 |
| 工作温度 | 0-50°C/ 32-122°F |
| 存储温度 | 0-50°C/ 32-122°F |
| 工作湿度 | 5 - 95%RH |
| 存储湿度 | 5 - 95%RH |
| 静电防护 | 15KV |
| 重量 | 1.5Mg |





OCBS-W234





OCBS-W234





OCBS-W234





OCBS-W234





OCBS-W234





OCBS-W234





OCBS-W234





OCBS-W234



□□□□:

[OCBS -W234](#)□□□□□□□□