

1D 2D

M / N OCBS -W238

- 1.
2. 1D 2D 4mil
3. USB 4.2 2.4G
4. 20
5. 50 PC
- 6.

	OCBS -W238
	DC 5V @ 250mA
	Type-B
	USB 2.4G 4.2
	ARM32
	USB
	1.5M
	30 30 .60°C -20°C
	CMOS.
	1.3M CMOS Global EX AAA1 URE
	100/
	50mm 900mm
	±360° ±60° ±55°
	40° x 30°
	≥25 PC
	2.4GHz 70; 30
	350KB 20,000
	5000mah.
	7

□□□□□□	≥36□□
□□□□	1□□
□□□□	1D□UPC-A□UPC-E□EAN-8□EAN-13□CODE 128□GS1-128□□□39□□□32□□ □93□□□11□5□5□5□□□2□□□2 5□□□2/5□□Codabar□NW-7□GS1 Databar□□ □□□□□□□□□□QR□□□QR□□□□□□□□PDF417□Micro PDF 417□AZTEC□□
□□□□	
□□	□□710□
□□	230 * 130 * 132mm
□□	
□□□□□□□□	0□45□□□□10□□80□□□□□□
□□□□□□□□	-20□60□□□□10□□90□□□□□□



OCBS-W238





OCBS-W238





OCBS-W238





OCBS-W238





OCBS-W238





OCBS-W238

