

# OCPP-80G 80mm diameter thermal printer

Resolution	230dots/line 260dots/line
Print speed	79.5±0.5mm/s
Print diameter	Φ80mm
Print thickness	0.06-0.08mm
Print density	576dots / line 512dots/line
Print resolution	3.75dots/mm
Interface	ESC / POS
Connectivity	Parallel + USB + LAN / 36Pin/25Pin + USB / LAN
Print volume	100pages
Print speed	100pages
Print memory	2048Kbytes
NV memory	256Kbytes
Power supply	AC110V / 240V 50/60HZ
DC supply	DC 24V / 2.5A
DC supply	DC 24V / 1A
Operating temperature	0-45°C / 10-80°C N- 0-45°C
Storage temperature	0-45°C / 10-80°C N- 0-45°C
Humidity	10-60°C; 10-90%
Font	ANK FontA 1.5 * 3.0 / FontB 1.1 * 2.1
Barcode	UPC-A / UPC-E / JAN EAN13 / JAN8 EAN8 / CODE39 / ITF / CODE93 / CODE128 / PDF417
Character set	PC347 PC850 PC860 PC863 PC865 WPC1252 PC866 2 PC852 2 PC858 IranII PT151 1251
Dimensions	1.25mm; 190x145x143mm * * *

## Notes

\*

\* IP

\*

\* Windows

\* Linux

\*

\*