

□□□

□□8□□□□□□□□

□□□□□□□□□□□□□□

□□□□□□□□□□

100M□□□□□□□□□□□□□□

256KB NV Logo □□□ 256kb □□□□□□□□

□□OPOS/JPOS□□□□

100KM□□□□□□□□

□□□□□

□□□□	□□□□
□□	ESC□/POS
□□□□	576 □/□□ 5 1 2□/□
□□□□	□□=72mm
□□□□	□□□□□
□□	U SB / UL /U +BT / U+WIFI
□□□□	200 □□/□□U □ 2 60□□ /□ (UL)
□□□□	80mm
□□□□	0.06~0.08mm
□□	□□□□□□∅ 83 □□
□□	□□□□□□□□□□
□□□□□□	256kbytes
NV□□	256kbytes
□□□□	□□A□12*24□□□□□□□□B□9*17
□□	GB18030,BIG5 24x24dots
□□/□□	□□
□□□□□□□□	PC347(□□□□),□□□□,PC850(□□□□),PC860(□□□□□),PC863(□□□□-□□),PC865(□□),□□,□□□□,□□□□,□□,□□,□□, WPC1252,PC866(□□□□□□#2), PC852(Latin2), PC858,IranII,□□□□□□,□□□□□□,PT151(1251) □□
□□	UPC-A/UPC-E/JAN13 □ EAN13 □ /JAN8 □ EAN8 □ /CODE39/ITF/CODABAR/CODE93/CODE128
□□	□□□□□□USB□UR□□□□ □□□□□□□□
□□□□□□	100 □□
□□□□	□□
□□□□	□□_
□□□□	□□□□□□□□□□□□□□□□□□□□□□
□□	□□ 100V-240V 50/60HZ
□□	□□ 24V/2.5A
□□□□	0°C~45°C, 10%~80%RH
□□□□	-10°C-60°C, 10%~90%RH
□□	□□□□□□□□□□□□□□□□□□□□CD□□□□□□□□□□□□□□□□
□□	1 80 (D)x14 2 (W)x13 6 (H)mm
□□	1.14 □□
□□□□	1. 8□□
□□	Windows XP /Vista/ Win7/Win8 /Win10/Win 2000/Win CE/OPOS/JPOS
SDK	□□□□IOS













