

58MM 58mm 58mm

OCPP-C582)

1. 120 mm/s

1. 120 mm/s
- 2.
- 3.
4. USB
5. USBBT,USBWIFI
- 6.
7. nv logo

2.

	OCPP-C582
	58mm
	USB / /RS232/ /USB/USBwifi/ USBL N
	I 100V-240V,50-60Hz , 12V/ 2.6 A
	12V/1A
	50KM
	128K NV Flash 4M
	,CD,
	iOS/Windows/Linux
	CE/FCC/Rohs
	203 DPI
	120/
	48mm
	3.75
	A32/ B42/ 16
	/POS
	UPC-A/UPC-E/JAN13/EAN13/18/EAN8/ CODE39/ITF/CODABAR/CODE93/CODE128
	384/ANK A12*241.5(W)*3.0(H) mm B9*17 1.1()*2.1()mm /24*24 3.0()*3.0()mm

□□	PC347□□□□□□/□□□ PC850□□□□□□ / PC860□□□□□□ PC863□□□□□□ / PC865□□□□□□ □□ / □□□ / □□□□ / □□ / □□ WPC1252 / PC866□□□□#2□ / PC852□□□□2□ PC858 / □□□□ / □□□□□□ / □□□□ / PT151□1251□
□□	
□□□□	□□□□
□□□□	57.5±0.5mm
□□□□	□□ 60mm
□□□□	0.06-0.08mm
□□□□	
□□	170*120*120mm
□□	1.3□□
□□□□	220*200*150 □□
12□1□□	670*325*425mm/16.5kg
□□	
□□□□ □□ □ □□	0 □ 4 5 □□□ , 10%~80% □□□
□□ □□ □ □□	-20 □ 60 □□□ , 10%~90% □□□







注意：切刀被卡住操作方法
将头盖打开盖盖，使打印头切刀复位。如不能复位，
打印结束，手动调节内旋钮，慢慢转动使切刀退回。

POWER STATUS FEED















