

58

(M/N: OCPP-M06)

□□□

1. □□□□□□□□□□
2. □□Windows□Java□Linux□Android□□AndroidIOS□□□□□
3. □□□□□USB □ RS232 □□
4. □□□ Android □ SDK
5. □□□□□□□□ □ 8 □□□□□□7 □ Android□1 □ Appl□ □□□visa □□
6. □□□□□□□□□ 1500□□), 4~5□□□
7. □□□□□□□□□ □□□□□ ,□□□□□□□□□□□□
8. □□□□□□□ 90 □□/□
9. 5 0□□ □□□□□□□
10. □□□□□□
11. E SC/POS □□□□□

□□

□□	OCPP-M06
□□	58mm□□□□□□□□□□□□
□□	□□□
□□	USB , RS-232 , □□□□□□
□□	7.4V DC/ 1500mAh □□□□□□□□
□□□□□	□□ 9v/1.5-2A
□□□□	□□□□ 4-5 □
□□	□□□□□□□□20K□Flash□256K
□□□□	□□□□□□□□□□□□□□□□□□
□□□□	□□□
TPH □□	50□□
□□	□□□□□□□□“1234”□□□□□□□□□□ □□□ □□ 6 □□□
□□	□□□□□□□□□□□□□□ rd ,□□,CD,□□□
□□□□□□	3.5*1.1mm
□□□□□□	Windows &Android & IOS □□
□□□□	CE□FCC□Rohs □
□□	
□□□□	□□□
□□□	203DPI□8□/□□□
□□□□	7 0□□/□ □□□ 90 □□/□□
□□□□	48□□
□□□□	120 □□□□□□□□□□□□
□□□□□	□□ A□ 32 □□/□ □□□□□□□ :16 □□/□
□□□□	□□□□/POS
□□	
□□□□	□□ A: 12*24dots, 1.5(W)*3.0(H) □□/□□□24*24dots, 3.0(W)*3.0(H)mm
□□□	□□□□/□□□□
□□	
□□□□	□□□□
□□□□	57.5 ±0.5 mm

□□□□	□□□□
□□□□	□□ 40 □□
□□□□	0.06-0.08mm
□□□□	
□□	105*75*45mm
□□	□□□360g □□□440g
□□□	190*120*70 □□
40 □ 1 □	380*475*340mm/18.36kg
□□	
□□□□ □□ □ □□	0 □ 4 5 □□□ , 10%~80% □□□
□□ □□ □ □□	-20 □ 60 □□□ , 10%~90% □□□





ocom
At your side

MODE POWER FEED



OCPP-M06

58MM Portable Thermal Printer



ocom
All your data

MODE POWER FEED

OCPP-M06
58MM Portable Thermal Printer

COM

USB



