

□□□□□□□□□□□□□□□□
□M / N□OCBS-T203□

□□□□□

□□□□□	CMOS
□□	752 * 480 CMOS
□□	□□□LED
□□	Code128□UCC / EAN-128□AIM-128□EAN-8□EAN-13□ISBN / ISSN□UPC-E□UPC-A□Interleaved 2 of 5□ITF-6□ITF-14□Matrix 2 of 5□□□25□□□25□Code 39□Codabar□Code 93□Code 11□Plessey□MSI-Plessey□GS1-DataBar□RSS□□RSS-14□RSS-Limited□RSS-Expand□
	PDF417□QR□□QR1 / 2□□□□□□□□□□ECC200□ ECC000,050,080,100,140□□□□□□
□□	≥5□□
□□□□	2.5□/□
□□□□	±50°@ 0°□□□0° Storto
	±360°@ 0°□□□0° Storto
	Storto ±60°@ 0°□□□0° □□
□□	USB HID-KBW□□□USB□□□USB HID-POS TTL-232□RS-232
□□	□□44°□□□33.2°
□□□	EAN-13 0□□-20□□□13mil□
	PDF 417 0□□ - 7□□□6.67mil□
	□□39 0□□-12□□□5□□□□□1□
	□□□□ 0□□ - 4□□□10MIL□
	□□□□ 0□□-10□□□15□□□
□□□L * W * H.□	89 * 108 * 143mm□□2□
□□	245□□□□□□□□□□
□□□□	20°C□+ 50°C □-4°F~122°F□
□□□□	-40°C□+ 80°C □-40°F~176°F□
□□	5□~95□□□□□□□□
ESD	±14□□□□□□□□□□±8□□□□□□□□
□□	□□□□1.2□□□□□□□□□□□□
□□	IP 52



OCBS-T203





OCBS-T203



