

# (POS-1508) POS

M / N POS-1508

OCOM POS Android windows OS MSR VFD / O

Msata SSD 64GB SSD 128GB 256GB

MSR VFD220

	POS-15 08 -W	POS-15 08 -A
	15.8 Windows POS	15.8 pos
	ABS	
	15.8	
	1920 * 1080	
	3.50cd / m <sup>2</sup>	
	1.60 1.50	
	G+G	
	15.8 15.6 1920 * 1080	
	Intel Celeron Bay Trail J1900 2.0GHz Intel core I3 / I5 4 CPU	ARM Cortex-A17 -RK 3288 1.8GHz CPU
	1 * SO-DIMM DDRIII 1333 * / 1600 4GB 2GB / 8GB	2GB DDRIII 4GB
	Msata SSD 64GB 256GB	16GB eMMC 32GB TF
	Real Tek ALC662 ALC5640	Real Tek ALC5640

网卡	10 / 100Mbps, Realtek RTL8111F 网卡 Mini PCI-E 网卡 WiFi 网卡	10M / 100M RTL8201F 网卡 100M / 1000M RTL8211E 网卡
操作系统	Windows 7/8/10 系统 WEPOS 系统 Linux	Android 8.1
分辨率	640 * 480 CMOS 摄像头	
功耗	4 小时 3W 功耗	
尺寸	58/80 毫米	
接口		
I/O 接口 RK3288 芯片	USB * 1	
	12V DC 接口 * 1	
	RJ-45 * 1	
	USB * 5	
	TF 卡 * 1	SIM 卡 * 1
	RJ11 * 1	
性能		
启动时间	0.4 秒	
待机时间	- 1 小时 60 分钟	
充电时间	10% ~ 80% 充电	
放电时间	10% ~ 90% 放电	
电源		
输入电压	110-240V / 50-60HZ AC 输入 DC12 V / 5A 输出	
输出	摄像头 / 摄像头	
接口	摄像头	
认证		
认证	FCC A 类 / CE 认证 / LVD / CCC	

摄像头









