

15.1 POS

(M/N: POS-1513P)

OCOM 1513P POS intel Celeron intel core I CPU 2ND MSR VFD

□□



Intel Celeron Intel Core I3 I5

Msata SSD 64GB SSD 128GB 256GB

□□□□□□□□

3 MSR VFD220

□□□□□□□□

□□

□□□□□□□□□□□□□□□□□□□□□□

□□□□□□□□□□□□□□□□□□□□□□

□□□□□□□□□□□□□□□□□□□□□□

□□□□□□□□□□□□□□□□□□□□□□

□□

□□	POS-1513P
□□	15.1□□□□□□ POS □□
□□	□□□□□□□□□□□□
□□	□□□□
□□	
□□□	15.1□□□□□□□□□□
□□□	1024*768
□□	250cd/□□□
□□	□□□□160□□□□150
□□□	□□□□GG□□□□
□□	9.7□□□□□□□□□□□□□□
□□	2*20 VFD □□□□□□□□□□□□
□□	
□□	Intel Celeron J4125, 2.0GHz □ intel core I3 / I5 4th CPU □□□□
□□□□	1*SO-DIMM DDR4□□□□□□2400mHZ□4GB/8GB□□
□□□□	Msata SSD 64GB □□□□□□ 256GB
□□	□□ Real Tek ALC662
□□□	10/100Mbs□Realtek RTL8111F □□□□ □□Mini PCI-E□□□□□□□□WIFI□□
□□□□	□□Windows 10/11
□□□	

接口 接口/接口(J4125)	接口*1
	12V DC 接口*1
	接口RJ-45*1
	USB*6
	15PIN D-sub VGA *1
	RS232*2
	接口*1接口*1
接口	
MSR	3接口MSR
接口	
接口	0接口40接口
接口	-10接口60接口
接口	10%~80% 接口
接口	10%~90% 接口
接口	
接口	接口5.5Kg接口7.0Kg
接口	440*290*425接口
接口	
接口	110-240V/50-60HZ接口接口DC12V/5A接口
接口	接口接口/接口/接口
接口	
接口	FCC A 接口/CE 接口/LVD/CCC













