

15.6 Windows/Android POS 终端

(M/N POS-1516)

OCOM POS 终端支持 Android/Windows 2nd 代 MSR VFD 终端
支持 I/O 接口

终端



15.6英寸终端

终端

终端

终端

终端

终端

□□□□□□□□

□□□□□□□□□□□□□□

□□□□□□□□□□□□□□MSR□□□□□□

□□

□□	POS-1516-W	POS-1516-A
□□	15.6□□Windows□□□□POS□□	15.6□□□□□□□□POS□□
□□	ABS□□□□□□□□□□	
□□	□□□□□	
□□		
□□□	15.6□□□□□□□□	
□□□	1366*768□1920*1080□□	
□□	300cd/□□□	
□□	□□□□160□□□□150	
□□□	□□□□GG□□□□	
□□	15.6□□□□□□□□□□□□□□□□1366*768□1920*1080□□□□□□	
□□	2*20 VFD□□□□□□□□□□	
□□		
□□	Intel Celeron Bay Trail J4215 2.0GHz □□□ intel core i3 / i5 □□□ CPU □□□□	RK3566□□□1.8GHz CPU
□□□□	1*SO-DIMM DDR4□□□□□2400 mHz 4GB□□□□8GB□□	□□2GB DDRIII□4GB□□□□
□□□□	Msata SSD 64GB □□□□□□ 256GB	8GB eMMC□□□32GB TF□□□
□□	□□Real Tek ALC662□□□□ALC5640	□□Real Tek□□□□ALC5640
□□□	10/100Mbps,Realtek RTL8111F □□□□ □□Mini PCI-E□□□□□□□□WIFI□□	10M/100M RTL8201F,10M/100M/1000M RTL8211E□□
□□□□	Windows7/8/10, □□□,WEPOS, Linux	Android 7.1 □ Android 8.1 □□□□
□□□		
□□/□□□□□□4125□□RK3566□	□□□□*1 12V DC □□□□*1 □□□□RJ-45*1 USB*4 □□(RS232) * 1 VGA(15□□D-sub)*1 □□□□*1	□□(RS232) * 2 RJ11 □□*1 □□□□□*1□□□□□*1
□□		
□□□□	0□40□□□	
□□□□	-10□60□□□	
□□□□	10%~80% □□□	
□□□□	10%~90% □□□	
□□		
□□□□□	110-240V/50-60HZ□□□□□□□□DC12V/5A□□□□□	
□□□	□□□□□□□□□□□□□□□□□□	
□□	□□□□□□□□□□□□	
□□		
□□	FCC A □□CE □□LVD/CCC	

















□□□□

[POS-1516 I5□□□□](#)

[POS-1516 J4125□□□□](#)