

# 15.6 / 15.1 / 12.1 POS

## M / N POS -C15 / C12

### OS

Windows 1900 2.0GHz CPU  
 Android 1.8GHz RK3288 Cortex-A17  
 2GB RAM + 8GB ROM Android  
 2GB RAM + 32GB SSD Windows  
 11.6 / 15.6  
 58 / 80mm  
 VFD

### Display

15.6 / 15.1 / 12.1 TFT LCD  
 1366 x 768  
 350cd / m<sup>2</sup>  
 60mm / s 150mm / s

### Input



### OS

OS①	Windows7
OS②	Android 5.1
RAM	2GB RAM 8GB ROM Android
Storage	SSD 32GB Windows
Display	15.6 / 15.1 / 12.1 TFT LCD
Brightness	350cd / m <sup>2</sup>
Resolution	1366 x 768
Resolution	203DPI
Resolution	ESC / POS
Resolution	60mm
Resolution	58mm 80mm
Resolution	60mm / s 150mm / s
Resolution	MCBF 50
Resolution	MSR / VFD 220 / 140
Resolution	150; 140

	1 * 12V DC * 1
	HDMI * 1
	VGA 15Pin D-sub * 1
I / O J1900	LAN RJ-45 * 1
	USB 2.0 * 4
	RS232 * 2
	MIC IN * 1 * 1
	RJ11 * 1
	TF * 1
I / O A83T	RJ45 * 1
	HDMI
	DB9 RS232 * 1 USB * 2
	* 1
	0°C ~ 40°C
	-20°C ~ 60°C
	Windows XP Embedded WE POS Linux
	110-240V / 50-60HZ DC12 / 5A