

15.6 15.1 POS POS

(M/N:POS-G156/G151)

OCOM Gpos... IO ...

I3 I5

Msata SSD 64GB SSD 128GB 256 GB

58mm 80mm

MSR VFD220

	POS-G156W/A	POS-G151W/A
	15.6 POS	15.1 POS
	15.6	15.1
	1366*768	1024*768
	250cd/m2	
	160*150	
	GG	
	15.6 13.3 1366*768	15.1 1024*768
	2*20 VFD	
J1900	Celeron Bay Trail J1900 2.0GHz intel core I3 / I5 4th CPU	
	1*SO-DIMM DDRIII 1333*/1600 4GB 2GB/8GB	
	Msata SSD 64GB 256GB	
	Real Tek ALC662	
	10/100Mbs, Realtek RTL8111F Mini PCI-E WIFI	
	Windows 7/8/10, POS, Linux	
RK3288	RK3288 1.8G RK3399	
	DDRIII 2GB 4GB	
	16GB EMMC 32GB	
	Real Tek ALC5640	
	10/100Mbs, Realtek RTL8111F	
	WIFI&BT Wi-Fi 802.11b/g/n, BT3.0/BT4.0	
	7.1	

Windows □ Android(J1900&RK3288)	□□ □□*1
	12V DC □□□□*1
	□□□RS232□* 1
	□□□□RJ-45*1
	USB *5
	□□□□*1 , □□□□*1
□□□J1900□	LPT *1
	VGA(15Pin D-sub)*1
	□□□ RJ11 *1□□□□
	PS/2 *1 □□□□□□
□□ (RK3288)	□□□ □□□RJ11*1□□□□□□□□□□RJ11*1□□□□
	TF□□*1
□□	
80mm□□□□□	□□□□□□
	150mm/s □□□□
	79.5-/ 0.5mm □□□□□□□□□□ 72mm
	□□□□□□□□□□□□□□100km
	USB □□
58mm□□□□□	□□□□□□
	80mm/s □□□□
	57.5-/ 0.5mm □□□□□□□□ 48mm
	□□□□□ 50km
	LPT □□
MSR	□□□ MSR □□□□ 15.6 □□
□□□□□	□□□□□□□□□□□□□□□□
□□□	□□ 80hm/5W □□□□□□□
□□	□□
□□	15.6□□□□6.5Kg□□□□8.5Kg
□□□□□□□	300*465*500mm
□□	
□□□□	0 □ 40 □□□
□□□□	-10 □ 60 □□□
□□□□	10%~80%
□□□□	10%~90%
□□	
□□□□□	110-240V/50-60HZ□□□□□□ ,DC12/5A □□□□□□ 58mm □□□□□□□□□□ DC12V/7A □□□□ W/80mm □□□□□□□□
□□□	□□□□□□□□□□/□□/□□□□□□□□
□□	□□□□□□□□□□□□
□□	
□□	FCC A □/CE □□/□□□□/□□□□

All In One Touch Screen POS System



Product Display

The whole machine featured anti-static protection, stronger EMI anti-interference, anti-ESD up to 8KV



Accessories



Thermal Printer



Barcode Scanner



Cash Drawer



Card Reader



Product
Accessories

SUPPORT SYSTEMS



WINDOWS



ANDROID




LINUX

Product Interface


Windows interfaces J1900




DC




LPT




COM



VGA



LAN



RJ11(optional)



USB 3.0*1



USB 2.0*4



PS/2



MIC-IN



LIN-OUT


Windows interfaces i3/i5




DC




HDMI



VGA



LAN



RJ11(optional)



USB 2.0*4



USB 3.0*1



MIC-IN




LIN-OUT


Android interfaces RK3288




DC



COM



LAN



RJ11(optional)*2



USB 3.0*1



USB 2.0*4



TF Card



MIC-IN



LIN-OUT

Screen Size



↙↘ 15.6 inch

or



↙↘ 15.6 inch

+

15.6 inch

13.3 inch

2*20 VFD



↙↘ 15.1 inch

or



↙↘ 15.1 inch

+

15.1 inch

2*20 VFD

Product Color



Product Details





